

P/N MS21060-3

Description

Thread: 10-32, self locking, two lug, floating, low height, corrosion resistant steel, silver plated, plain rivet holes, MS21060 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS210603

Minimum Qty (MOQ): 25

NSN: 5310-00-783-4174

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N MS21060-3 Specifications

Thread Direction: Dread Direction: Right-hand Locking Feature: Mounting Hole Diameter: Nut Style: Nut Length: Nut Length: 0.948 Inches Maximum Nut Height: 0.948 Inches Maximum Nut Height: 0.920 Inches Maximum Nut Height: 0.920 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: Distance From Aperture Center To Mounting Hole Center To Mounting Holes Along Length: Center To Center Distance Between Mounting Holes Along Length: Temp Rating: Book Deg Fahrenheit Nominal Thread Series: Center To Center Distance Between Mounting Holes Along Length: Thread Series: Thread Quantity Per Inch: Hardness Rating: A9.0 Rockwell C Maximum Nominal Thread Size: Material: Material: Material Document And Classification: Silver Overall Sulface Treatment Document And Classification: Ams 2410 Assn Std Single Treatment Response Overall Center Treatment Response Overall Ams 2410 Assn Std Single Treatment Response Overall Center Teatment Poocument And Classification: Ams 2410 Assn Std Single Treatment Response Overall Center Teatment Document And Classification: Ams 2410 Assn Std Single Treatment Response Overall	-1 10	
Locking Feature: Prevailing Torque All Metal Design Mounting Hole Diameter: 0.098 Inches Minimum And 0.103 Inches Maximum Nut Style: Plate Nut Length: 0.948 Inches Maximum Nut Height: 0.250 Inches Maximum Plate Thickness: 0.032 Inches Maximum Plate Width: 0.290 Inches Minimum And 0.416 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Arrangement Style: 3.39 Inches Minimum And 0.349 Inches Maximum Center: O.686 Inches Minimum And 0.690 Inches Maximum Oles Along Length: 80.0 Deg Fahrenheit Nominal Therad Series: Unif Features Provided: Floating Nut Thread Quantity Per Inch: 3.90 Rockwell C Maximum Nominal Thread Size: 49.0 Rockwell C Maximum Nominal Thread Size: 10.10 Inches Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Sing	Thread Class:	3b
Mounting Hole Diameter: 0.098 Inches Minimum And 0.103 Inches Maximum Nut Style: Plate Nut Length: 0.948 Inches Maximum Nut Height: 0.250 Inches Maximum Plate Thickness: 0.032 Inches Maximum Plate Width: 0.290 Inches Minimum And 0.416 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole 2 Holes Center To Center Distance Between Mounting Holes Along Length: 0.686 Inches Minimum And 0.349 Inches Maximum Temp Rating: 80.0 Deg Fahrenheit Nominal Thread Series: 90.0 Deg Fahrenheit Nominal Thread Quantity Per Inch: 2 Hardness Rating: 9.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material Document And Classification: 2ms 5252 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Overall	Thread Direction:	Right-hand
Nut Style: Plate Nut Length: 0.948 Inches Maximum Nut Height: 0.250 Inches Maximum Plate Thickness: 0.322 Inches Maximum Plate Width: 0.290 Inches Minimum And 0.416 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.339 Inches Minimum And 0.349 Inches Maximum Center: 0.686 Inches Minimum And 0.690 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 800.0 Deg Fahrenheit Nominal Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 32 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Am 5525 Asan Std Single Material Response Overall Or Ams 5732 Asan Std Single Material Response Overall Precious Material: Silver Overall	Locking Feature:	Prevailing Torque All Metal Design
Nut Length: 0.948 Inches Maximum Nut Height: 0.250 Inches Maximum Plate Thickness: 0.032 Inches Maximum Plate Width: 0.290 Inches Minimum And 0.416 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole 3.339 Inches Minimum And 0.349 Inches Maximum Center To Center Distance Between Mounting 0.686 Inches Minimum And 0.690 Inches Maximum Holes Along Length: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: 1 Floating Nut Thread Quantity Per Inch: 32 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: Iron Alloy 660 Overall Material Document And Classification: 3737 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Precious Material: Silver Overall	Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Height: 0.250 Inches Maximum Plate Thickness: 0.032 Inches Maximum Plate Width: 0.290 Inches Minimum And 0.416 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.339 Inches Minimum And 0.349 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.686 Inches Minimum And 0.690 Inches Maximum Temp Rating: 0.00.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 32 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: Iron Alloy 660 Overall Material Document And Classification: 6737 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Precious Material: Silver	Nut Style:	Plate
Plate Width: 0.032 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.339 Inches Minimum And 0.349 Inches Maximum Center Distance Between Mounting Holes Along Length: 0.686 Inches Minimum And 0.690 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 32 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: 10.190 Inches Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Nut Length:	0.948 Inches Maximum
Plate Width: 0.290 Inches Minimum And 0.416 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.339 Inches Minimum And 0.349 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.686 Inches Minimum And 0.690 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 32 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Nut Height:	0.250 Inches Maximum
Nut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.339 Inches Minimum And 0.349 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.686 Inches Minimum And 0.690 Inches MaximumTemp Rating:800.0 Deg Fahrenheit NominalThread Series:UnjfFeatures Provided:Floating NutThread Quantity Per Inch:32Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.190 InchesMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall	Plate Thickness:	0.032 Inches Maximum
Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.339 Inches Minimum And 0.349 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.686 Inches Minimum And 0.690 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 32 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Plate Width:	0.290 Inches Minimum And 0.416 Inches Maximum
Distance From Aperture Center To Mounting Hole Center: 0.339 Inches Minimum And 0.349 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.686 Inches Minimum And 0.690 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 32 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Nut Mounting Provision:	Straight Holes
Center To Center Distance Between Mounting Holes Along Length: Temp Rating: No. 0.686 Inches Minimum And 0.690 Inches Maximum Bound Length: Temp Rating: No. 0.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Incomparison of Maximum Thread Quantity Per Inch: Hardness Rating: Nominal Thread Size: Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Mounting Hole Arrangement Style:	2 Holes
Holes Along Length: Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 32 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: Iron Alloy 660 Overall Material Document And Classification: 5737 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	-	0.339 Inches Minimum And 0.349 Inches Maximum
Thread Series: Features Provided: Floating Nut Thread Quantity Per Inch: 32 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	_	0.686 Inches Minimum And 0.690 Inches Maximum
Features Provided: Thread Quantity Per Inch: 32 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Temp Rating:	800.0 Deg Fahrenheit Nominal
Thread Quantity Per Inch: Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Thread Series:	Unjf
Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Features Provided:	Floating Nut
Nominal Thread Size: Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Thread Quantity Per Inch:	32
Material:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall	Hardness Rating:	49.0 Rockwell C Maximum
Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Silver Overall	Nominal Thread Size:	0.190 Inches
Precious Material: Surface Treatment: 5737 Assn Std Single Material Response Overall Silver Silver Overall	Material:	Iron Alloy 660 Overall
Surface Treatment: Silver Overall	Material Document And Classification:	
	Precious Material:	Silver
Surface Treatment Document And Classification: Ams 2410 Assn Std Single Treatment Response Overall	Surface Treatment:	Silver Overall
	Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall

How to Order

