

P/N MS21060-4

Description

Thread Size: 1/4", Nut Length: 1-1/4", Nut Height: 1/4", two lug, locknut, MS21060 series nut

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS210604

Minimum Qty (MOQ): 10

NSN: 5310-00-780-1041


Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







^{*} See page 2 for technical characteristics

P/N MS21060-4 Specifications

Thread Direction: Locking Feature: Mounting Hole Diameter: Nut Style: Nut Length: Nut Height: Nut Height: Nut Height: Nut Height: Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: Nut Mounting Hole Arrangement Style: Straight Holes Mounting Hole Arrangement Style: Distance From Aperture Center To Mounting Hole Center To Center Distance Between Mounting Holes Along Length: Temp Rating: Center To Center Distance Between Mounting Holes Along Length: Thread Series: Chard Series: Holas Mounting Provided: Thread Quantity Per Inch: Hardness Rating: An 9.0 Rockwell C Maximum Nominal Thread Size: Material: Material Document And Classification: Silver Sulface Treatment Document And Classification: Ams 2410 Assn Std Single Material Response Overall Center Treatment Document And Classification: Ams 2410 Assn Std Single Treatment Response Overall Character Teatment Pocument And Classification: Ams 2410 Assn Std Single Treatment Response Overall Character Teatment Document And Classification: Ams 2410 Assn Std Single Treatment Response Overall Character Teatment Document And Classification: Ams 2410 Assn Std Single Treatment Response Overall Character Teatment Document And Classification: Ams 2410 Assn Std Single Treatment Response Overall	-, , ,,	
Locking Feature: Prevailing Torque All Metal Design Mounting Hole Diameter: 0.098 Inches Minimum And 0.103 Inches Maximum Nut Style: Plate Nut Length: 1.292 Inches Maximum Nut Height: 0.381 Inches Maximum Plate Thickness: 0.322 Inches Maximum Plate Width: 0.350 Inches Minimum And 0.516 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Arrangement Style: 2 Holes Center Postance Between Mounting Hole Arrangement Style: 0.495 Inches Minimum And 0.505 Inches Maximum Close To Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Tomas Along Length: 0.00 Deg Fahrenheit Nominal Thread Series: Unif Features Provided: 10 Foot Signal Nutril Style Inches Maximum Thread Quantity Per Inch: 28 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 10 Foot Along Geo Overall Material Document And Classification: Ams 5735 Asas Std Single Material Response Overall Or Ams 5737 Asas Std Single Material Response Ove	Thread Class:	3b
Mounting Hole Diameter: 0.098 Inches Minimum And 0.103 Inches Maximum Nut Style: Plate Nut Length: 1.292 Inches Maximum Nut Height: 0.281 Inches Maximum Plate Thickness: 0.032 Inches Maximum Plate Width: 0.350 Inches Minimum And 0.516 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole 2 Holes Center To Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 0.505 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: 90.00 Deg Fahrenheit Nominal Thread Quantity Per Inch: 8 Hardness Rating: 9.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material Document And Classification: 3ms 7335 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Overall	Thread Direction:	Right-hand
Nut Style: Plate Nut Length: 1.292 Inches Maximum Nut Height: 0.281 Inches Maximum Plate Thickness: 0.322 Inches Maximum Plate Width: 0.350 Inches Minimum And 0.516 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.495 Inches Minimum And 0.505 Inches Maximum Center: 0.495 Inches Minimum And 1.002 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 80.00 Deg Fahrenheit Nominal Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unif Features Provided: Floating Nut Thread Quantity Per Inch: 28 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Or Ams 5	Locking Feature:	Prevailing Torque All Metal Design
Nut Length: 1.292 Inches Maximum Nut Height: 0.281 Inches Maximum Plate Thickness: 0.032 Inches Maximum Plate Width: 0.350 Inches Minimum And 0.516 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole 2 Holes Center To Center Distance Between Mounting 0.998 Inches Minimum And 0.051 Inches Maximum Clease To Center Distance Between Mounting 0.998 Inches Minimum And 1.002 Inches Maximum Holes Along Length: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: 1 Floating Nut Thread Quantity Per Inch: 28 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: 3525 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Overall	Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Height: 0.281 Inches Maximum Plate Thickness: 0.032 Inches Maximum Plate Width: 0.350 Inches Minimum And 0.516 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.495 Inches Minimum And 0.505 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Temp Rating: 0.900 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 28 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: 5525 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Overall	Nut Style:	Plate
Plate Width: 0.032 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.495 Inches Minimum And 0.505 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 28 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver	Nut Length:	1.292 Inches Maximum
Plate Width: 0.350 Inches Minimum And 0.516 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.495 Inches Minimum And 0.505 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 28 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver	Nut Height:	0.281 Inches Maximum
Nut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.495 Inches Minimum And 0.505 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.998 Inches Minimum And 1.002 Inches MaximumTemp Rating:800.0 Deg Fahrenheit NominalThread Series:UnjfFeatures Provided:Floating NutThread Quantity Per Inch:28Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.250 InchesMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall	Plate Thickness:	0.032 Inches Maximum
Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.495 Inches Minimum And 0.505 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 28 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Plate Width:	0.350 Inches Minimum And 0.516 Inches Maximum
Distance From Aperture Center To Mounting Hole Center: 0.495 Inches Minimum And 0.505 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 28 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Nut Mounting Provision:	Straight Holes
Center To Center Distance Between Mounting Holes Along Length: Temp Rating: No.998 Inches Minimum And 1.002 Inches Maximum 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Inread Quantity Per Inch: Hardness Rating: Nominal Thread Size: Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Sufface Treatment: Silver Overall	Mounting Hole Arrangement Style:	2 Holes
Holes Along Length: Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 28 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: S125 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	-	0.495 Inches Minimum And 0.505 Inches Maximum
Thread Series: Features Provided: Floating Nut Thread Quantity Per Inch: 28 Hardness Rating: A9.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	_	0.998 Inches Minimum And 1.002 Inches Maximum
Features Provided: Thread Quantity Per Inch: 28 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Temp Rating:	800.0 Deg Fahrenheit Nominal
Thread Quantity Per Inch: Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Thread Series:	Unjf
Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Features Provided:	Floating Nut
Nominal Thread Size: Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Thread Quantity Per Inch:	28
Material:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall	Hardness Rating:	49.0 Rockwell C Maximum
Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5525 Assn Std Single Material Response Overall Precious Material: Silver Silver Overall	Nominal Thread Size:	0.250 Inches
Precious Material: Surface Treatment: 5525 Assn Std Single Material Response Overall Silver Silver Overall	Material:	Iron Alloy 660 Overall
Surface Treatment: Silver Overall	Material Document And Classification:	
	Precious Material:	Silver
Surface Treatment Document And Classification: Ams 2410 Assn Std Single Treatment Response Overall	Surface Treatment:	Silver Overall
	Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall

How to Order

