

P/N MS21060-5

Description

Thread: 1/4-24, Thread Size: 1/4", Length: 1-1/4", Nut Height: 3/8", two lug, floating, MS21060 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

10AX86A507N81

SKU / Model: MS210605

Minimum Qty (MOQ): 10

NSN: 5310-00-779-6769

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







P/N MS21060-5 Specifications

Thread Direction: Locking Feature: Prevailing Torque All Metal Design Mounting Hole Diameter: Nut Style: Nut Length: Nut Length: Nut Height: Nut Height: Nut Height: Nut Height: Nut Mounting Provision: Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: Distance From Aperture Center To Mounting Hole Center: Center To Center Distance Between Mounting Holes Along Length: Supple Holes Holes Holes Holes Holes Holes Holes Along Length: Temp Rating: Holes Along Length: Features Provided: Holes Holes Along Length: Features Provided: Holes Holes Along Length: Features Provided: Holes Along Length: Holes Along Len	-, , ,,	
Locking Feature: Prevailing Torque All Metal Design Mounting Hole Diameter: 0.130 Inches Minimum And 0.135 Inches Maximum Nut Style: Plate Nut Length: 0.292 Inches Maximum Nut Height: 0.328 Inches Maximum Plate Thickness: 0.045 Inches Maximum Plate Width: 0.412 Inches Minimum And 0.609 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 2 Holes Center To Center Distance Between Mounting Hole Arrangement Style: 0.495 Inches Minimum And 0.505 Inches Maximum Toles Along Length: 0.998 Inches Minimum And 0.002 Inches Maximum Toles Along Length: 0.900 Deg Fahrenheit Nominal Thread Series: Unif Features Provided: 10 Footing Nut Thread Quantity Per Inch: 49.0 Rockwell C Maximum Nominal Thread Size: 30.12 Inches Material: 10 no Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Precious Material:	Thread Class:	3b
Mounting Hole Diameter: 0.130 Inches Minimum And 0.135 Inches Maximum Nut Style: Plate Nut Length: 1.292 Inches Maximum Nut Height: 0.328 Inches Maximum Plate Thickness: 0.045 Inches Maximum Plate Width: 0.412 Inches Minimum And 0.609 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Holes 2.495 Inches Minimum And 0.505 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Material Document And Classification: 2ms 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Precious Material: Silver Overall	Thread Direction:	Right-hand
Nut Style: Plate Nut Length: 1.292 Inches Maximum Nut Height: 0.328 Inches Maximum Plate Thickness: 0.045 Inches Maximum Plate Width: 0.412 Inches Minimum And 0.609 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.495 Inches Minimum And 0.505 Inches Maximum Center: 0.498 Inches Minimum And 1.002 Inches Maximum Center Distance Between Mounting Hole Salong Length: 0.998 Inches Minimum And 1.002 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 24 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Am 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or	Locking Feature:	Prevailing Torque All Metal Design
Nut Length: 1.292 Inches Maximum Nut Height: 0.328 Inches Maximum Plate Thickness: 0.045 Inches Maximum Plate Width: 0.412 Inches Minimum And 0.609 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole 0.495 Inches Minimum And 0.505 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unif Features Provided: Floating Nut Thread Quantity Per Inch: 24 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Material Document And Classification: 6737 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Precious Material: Silver Overall	Mounting Hole Diameter:	0.130 Inches Minimum And 0.135 Inches Maximum
Nut Height: 0.328 Inches Maximum Plate Thickness: 0.045 Inches Maximum Plate Width: 0.412 Inches Minimum And 0.609 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole 0.495 Inches Minimum And 0.505 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 24 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Material Document And Classification: 5537 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Nut Style:	Plate
Plate Thickness: 0.045 Inches Maximum Plate Width: 0.412 Inches Minimum And 0.609 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.495 Inches Minimum And 0.505 Inches Maximum Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 24 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Material Document And Classification: S525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Precious Material: Silver	Nut Length:	1.292 Inches Maximum
Plate Width: 0.412 Inches Minimum And 0.609 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.495 Inches Minimum And 0.505 Inches Maximum Center To Center Distance Between Mounting Poles Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 24 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Nut Height:	0.328 Inches Maximum
Nut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.495 Inches Minimum And 0.505 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.998 Inches Minimum And 1.002 Inches MaximumTemp Rating:800.0 Deg Fahrenheit NominalThread Series:UnjfFeatures Provided:Floating NutThread Quantity Per Inch:24Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.312 InchesMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall	Plate Thickness:	0.045 Inches Maximum
Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.495 Inches Minimum And 0.505 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 24 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Plate Width:	0.412 Inches Minimum And 0.609 Inches Maximum
Distance From Aperture Center To Mounting Hole Center: 0.495 Inches Minimum And 0.505 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 24 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Nut Mounting Provision:	Straight Holes
Center To Center Distance Between Mounting Holes Along Length: Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 24 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Sizes Sizes Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Precious Material: Silver Overall Surface Treatment: Silver Overall	Mounting Hole Arrangement Style:	2 Holes
Holes Along Length: Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 24 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Material Document And Classification: 5737 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	-	0.495 Inches Minimum And 0.505 Inches Maximum
Thread Series: Features Provided: Floating Nut Thread Quantity Per Inch: 24 Hardness Rating: A9.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	_	0.998 Inches Minimum And 1.002 Inches Maximum
Features Provided: Thread Quantity Per Inch: Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Precious Material: Surface Treatment: Silver Overall	Temp Rating:	800.0 Deg Fahrenheit Nominal
Thread Quantity Per Inch: Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Thread Series:	Unjf
Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Features Provided:	Floating Nut
Nominal Thread Size: Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Silver Overall	Thread Quantity Per Inch:	24
Material:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall	Hardness Rating:	49.0 Rockwell C Maximum
Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Silver Overall	Nominal Thread Size:	0.312 Inches
Material Document And Classification: 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Material:	Iron Alloy 660 Overall
Surface Treatment: Silver Overall	Material Document And Classification:	
	Precious Material:	Silver
Surface Treatment Document And Classification: Ams 2410 Assn Std Single Treatment Response Overall	Surface Treatment:	Silver Overall
	Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall

How to Order

