

P/N MS21060-6

Description

Thread Size: 3/8", Nut Length: 1-1/4", Nut Height: 3/8", MS21060 series nut

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS210606

Minimum Qty (MOQ): 5

NSN: 5310-00-779-6761

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







^{*} See page 2 for technical characteristics

P/N MS21060-6 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.435 Inches Minimum Nut And 0.455 Inches Maximum Nut
Mounting Hole Diameter:	0.130 Inches Minimum And 0.135 Inches Maximum
Nut Style:	Plate
Nut Length:	1.292 Inches Maximum
Nut Height:	0.344 Inches Maximum
Plate Thickness:	0.055 Inches Maximum
Plate Width:	0.475 Inches Minimum And 0.680 Inches Maximum
Nut Counterbore Depth:	0.055 Inches Maximum Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.495 Inches Minimum And 0.505 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.998 Inches Minimum And 1.002 Inches Maximum
Temp Rating:	800.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	24
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.375 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Precious Material:	Silver
Surface Treatment:	Silver Overall
Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall

How to Order

