

# P/N MS21060L08K

## **Description**

8-32 thread - self-locking nutplate - two lug floating - low height - corrosion resistant steel - 450°, - with dry film lube - countersunk rivet holes

\* Manufacturer certifications are shipped with your order FREE of charge

# Order this part online

### **Additional Information**

SKU / Model: MS21060L08K

Minimum Qty (MOQ): 10

NSN: 5310-00-779-6736

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS21060L08K Specifications

Thread Class: 3b  Thread Direction: Right-hand  Locking Feature: Prevailing Torque All Metal Design  Counterbore Diameter: 0.168 Inches Minimum Nut	
Locking Feature: Prevailing Torque All Metal Design	
Lubrication:  Dry Film Lubricant	
Mounting Hole Diameter: 0.098 Inches Minimum And 0.103 Inches Maximum	
Nut Style: Plate	
Nut Length: 0.948 Inches Maximum	
Nut Height: 0.250 Inches Maximum  0.233 Inches Maximum	
Plate Thickness: 0.032 Inches Maximum	
Plate Width: 0.290 Inches Minimum And 0.416 Inches Maximum	
Nut Counterbore Depth: 0.062 Inches Minimum Nut	
Nut Mounting Provision: Countersunk Holes	
Mounting Provision Location:  Opposite Nut Projection Side	
Mounting Hole Arrangement Style: 2 Holes	
Distance From Aperture Center To Mounting Hole Center:  0.339 Inches Minimum And 0.349 Inches Maximum	
Center To Center Distance Between Mounting Holes Along Length:  0.686 Inches Minimum And 0.690 Inches Maximum	
Temp Rating: 450.0 Deg Fahrenheit Nominal	
Thread Series: Unjc	
Features Provided: Floating Nut	
Thread Quantity Per Inch: 32	
Hardness Rating: 49.0 Rockwell C Maximum	
Nominal Thread Size: 0.164 Inches	
Mounting Hole Countersink Angle: 98.0 Degrees Minimum And 102.0 Degrees Maximum	
Material: Iron Alloy 660 Overall	
Material Document And Classification:  Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall	ms
Surface Treatment: Passivate Overall	

# **How to Order** Order this self-locking plate nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/MS21060L08K">https://military-fasteners.com/nuts/self\_locking+nutplates/MS21060L08K</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.