

P/N MS21060L3K

Description

10-32 thread, self-locking nutplate, two lug floating, low height, corrosion resistant steel, with dry film lube, countersunk rivet holes

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS21060L3K

Minimum Qty (MOQ): 20

NSN: 5310-00-779-6735

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS21060L3K Specifications

Thread Direction: Right-hand Locking Feature: Prevailing Torque All Metal Design Counterbore Diameter: 0.194 Inches Minimum Nut Lubrication: Dry Film Lubricant Mounting Hole Diameter: 0.098 Inches Minimum And 0.103 Inches Maximum Nut Style: Plate Nut Length: 0.948 Inches Maximum Nut Height: 0.250 Inches Maximum Plate Thickness: 0.032 Inches Maximum Plate Width: 0.290 Inches Minimum And 0.416 Inches Maximum Nut Counterbore Depth: 0.062 Inches Minimum Nut Nut Mounting Provision: Countersunk Holes Mounting Provision Location: Opposite Nut Projection Side Mounting Hole Arrangement Style: 2 Holes
Locking Feature:Prevailing Torque All Metal DesignCounterbore Diameter:0.194 Inches Minimum NutLubrication:Dry Film LubricantMounting Hole Diameter:0.098 Inches Minimum And 0.103 Inches MaximumNut Style:PlateNut Length:0.948 Inches MaximumNut Height:0.250 Inches MaximumPlate Thickness:0.032 Inches MaximumPlate Width:0.290 Inches Minimum And 0.416 Inches MaximumNut Counterbore Depth:0.062 Inches Minimum NutNut Mounting Provision:Countersunk HolesMounting Provision Location:Opposite Nut Projection Side
Counterbore Diameter: 0.194 Inches Minimum Nut Lubrication: Dry Film Lubricant Mounting Hole Diameter: 0.098 Inches Minimum And 0.103 Inches Maximum Nut Style: Plate Nut Length: 0.948 Inches Maximum Nut Height: 0.250 Inches Maximum Plate Thickness: 0.032 Inches Maximum Plate Width: 0.290 Inches Minimum And 0.416 Inches Maximum Nut Counterbore Depth: 0.062 Inches Minimum Nut Nut Mounting Provision: Countersunk Holes Mounting Provision Location: Opposite Nut Projection Side
Lubrication: Mounting Hole Diameter: 0.098 Inches Minimum And 0.103 Inches Maximum Nut Style: Plate Nut Length: 0.948 Inches Maximum Nut Height: 0.250 Inches Maximum Plate Thickness: 0.032 Inches Maximum Plate Width: 0.290 Inches Minimum And 0.416 Inches Maximum Nut Counterbore Depth: 0.062 Inches Minimum Nut Nut Mounting Provision: Countersunk Holes Mounting Provision Location: Opposite Nut Projection Side
Mounting Hole Diameter:0.098 Inches Minimum And 0.103 Inches MaximumNut Style:PlateNut Length:0.948 Inches MaximumNut Height:0.250 Inches MaximumPlate Thickness:0.032 Inches MaximumPlate Width:0.290 Inches Minimum And 0.416 Inches MaximumNut Counterbore Depth:0.062 Inches Minimum NutNut Mounting Provision:Countersunk HolesMounting Provision Location:Opposite Nut Projection Side
Nut Style:PlateNut Length:0.948 Inches MaximumNut Height:0.250 Inches MaximumPlate Thickness:0.032 Inches MaximumPlate Width:0.290 Inches Minimum And 0.416 Inches MaximumNut Counterbore Depth:0.062 Inches Minimum NutNut Mounting Provision:Countersunk HolesMounting Provision Location:Opposite Nut Projection Side
Nut Length:0.948 Inches MaximumNut Height:0.250 Inches MaximumPlate Thickness:0.032 Inches MaximumPlate Width:0.290 Inches Minimum And 0.416 Inches MaximumNut Counterbore Depth:0.062 Inches Minimum NutNut Mounting Provision:Countersunk HolesMounting Provision Location:Opposite Nut Projection Side
Nut Height:0.250 Inches MaximumPlate Thickness:0.032 Inches MaximumPlate Width:0.290 Inches Minimum And 0.416 Inches MaximumNut Counterbore Depth:0.062 Inches Minimum NutNut Mounting Provision:Countersunk HolesMounting Provision Location:Opposite Nut Projection Side
Plate Thickness: 0.032 Inches Maximum 0.290 Inches Minimum And 0.416 Inches Maximum Nut Counterbore Depth: 0.062 Inches Minimum Nut Nut Mounting Provision: Countersunk Holes Mounting Provision Location: Opposite Nut Projection Side
Plate Width: 0.290 Inches Minimum And 0.416 Inches Maximum Nut Counterbore Depth: 0.062 Inches Minimum Nut Nut Mounting Provision: Countersunk Holes Mounting Provision Location: Opposite Nut Projection Side
Nut Counterbore Depth:0.062 Inches Minimum NutNut Mounting Provision:Countersunk HolesMounting Provision Location:Opposite Nut Projection Side
Nut Mounting Provision: Countersunk Holes Mounting Provision Location: Opposite Nut Projection Side
Mounting Provision Location: Opposite Nut Projection Side
Mounting Hole Arrangement Style: 2 Holes
Producting note Arrangement Style.
Distance From Aperture Center To Mounting Hole Center: 0.339 Inches Minimum And 0.349 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length: 0.686 Inches Minimum And 0.690 Inches Maximum
Temp Rating: 450.0 Deg Fahrenheit Nominal
Thread Series: Unjf
Features Provided: Floating Nut
Thread Quantity Per Inch: 32
Hardness Rating: 49.0 Rockwell C Maximum
Nominal Thread Size: 0.190 Inches
Mounting Hole Countersink Angle: 98.0 Degrees Minimum And 102.0 Degrees Maximum
Material: Iron Alloy 660 Overall
Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall 5737 Assn Std Single Material Response Overall
Surface Treatment: Passivate Overall

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/MS21060L3K and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.