

Description

thread: 1/4-28, self locking, two lug floating, low height, corrosion resistant steel, with dry film lube, plain rivet holes, MS21060 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21060L4
Minimum Qty (MOQ):	10
NSN:	5310-00-779-6689
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS21060L4 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	1.292 Inches Maximum
Nut Height:	0.281 Inches Maximum
Plate Thickness:	0.032 Inches Maximum
Plate Width:	0.350 Inches Minimum And 0.516 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.500 Inches Nominal
Center To Center Distance Between Mounting Holes Along Length:	0.998 Inches Minimum And 1.002 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	28
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.250 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/MS21060L4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.