

**Description**

Thread Size: 1/4", Nut Length: 1", Nut Height: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS210613K                                 |
| Minimum Qty (MOQ):      | 10 EA                                     |
| NSN:                    | 5310-00-778-9291                          |
| Schedule B:             | 7318.16.0085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N MS21061-3K Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3b  |
| <b>Thread Direction:</b>  | Right-hand  |
| <b>Locking Feature:</b>   | Prevailing Torque All Metal Design                            |
| <b>Lubrication:</b>   | Dry Film Lubricant  |
| <b>Mounting Hole Diameter:</b>  | 0.098 Inches Minimum And 0.103 Inches Maximum                 |
| <b>Nut Style:</b>   | Plate   |
| <b>Nut Length:</b>  | 1.051 Inches Maximum  |
| <b>Nut Height:</b>  | 0.250 Inches Maximum  |
| <b>Plate Thickness:</b>   | 0.032 Inches Maximum  |
| <b>Plate Width:</b>   | 0.290 Inches Minimum And 0.422 Inches Maximum                 |
| <b>Nut Mounting Provision:</b>  | Countersunk Holes   |
| <b>Mounting Provision Location:</b>                                   | Opposite Nut Projection Side                                  |
| <b>Mounting Hole Arrangement Style:</b>                               | 2 Holes   |
| <b>Distance From Aperture Center To Mounting Hole Center:</b>         | 0.339 Inches Minimum And 0.349 Inches Maximum                 |
| <b>Center To Center Distance Between Mounting Holes Along Length:</b> | 0.310 Inches Minimum And 0.314 Inches Maximum                 |
| <b>Temp Rating:</b>   | 450.0 Deg Fahrenheit Nominal                                  |
| <b>Thread Series:</b>   | Unjf  |
| <b>Features Provided:</b>   | Floating Nut  |
| <b>Thread Quantity Per Inch:</b>                                      | 32  |
| <b>Hardness Rating:</b>   | 49.0 Rockwell C Maximum                                       |
| <b>Nominal Thread Size:</b>   | 0.190 Inches  |
| <b>Mounting Hole Countersink Angle:</b>                               | 98.0 Degrees Minimum And 102.0 Degrees Maximum                |
| <b>Material:</b>  | Steel Overall   |
| <b>Surface Treatment:</b>   | Cadmium Overall   |
| <b>Surface Treatment Document And Classification:</b>                 | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |

## How to Order

Order this plate - one lug locknut from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+nutplates/MS21061-3K](https://military-fasteners.com/nuts/self_locking+nutplates/MS21061-3K) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.