

## P/N MS21061L06K

### **Description**

6-32 thread, self-locking nutplate, one lug floating, low height, cadmium plated carbon steel, with dry film lube, countersunk rivet holes

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS21061L06K

Minimum Qty (MOQ): 25

NSN: 5310-00-778-9512

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS21061L06K Specifications

| Thread Class   | 2 h   |
|--|---|
| Thread Class:  | 3b  |
| Thread Direction:  | Right-hand  |
| Locking Feature:   | Prevailing Torque All Metal Design                  |
| Lubrication:   | Dry Film Lubricant                                  |
| Mounting Hole Diameter:  | 0.098 Inches Minimum And 0.103 Inches Maximum       |
| Nut Style:   | Plate   |
| Nut Length:  | 1.051 Inches Maximum                                |
| Nut Height:  | 0.203 Inches Maximum                                |
| Plate Thickness:   | 0.032 Inches Maximum                                |
| Plate Width:   | 0.290 Inches Minimum And 0.422 Inches Maximum       |
| Nut Mounting Provision:  | Countersunk Holes                                   |
| Mounting Provision Location:                                   | Opposite Nut Projection Side                        |
| Mounting Hole Arrangement Style:                               | 2 Holes   |
| Distance From Aperture Center To Mounting Hole Center:         | 0.339 Inches Minimum And 0.349 Inches Maximum       |
| Center To Center Distance Between Mounting Holes Along Length: | 0.310 Inches Minimum And 0.314 Inches Maximum       |
| Temp Rating:   | 450.0 Deg Fahrenheit Nominal                        |
| Thread Series:   | Unjc  |
| Features Provided:   | Floating Nut  |
| Thread Quantity Per Inch:                                      | 32  |
| Hardness Rating:   | 49.0 Rockwell C Maximum                             |
| Nominal Thread Size:   | 0.138 Inches  |
| Mounting Hole Countersink Angle:                               | 98.0 Degrees Minimum And 102.0 Degrees Maximum      |
| Material:  | Steel Overall                                       |
| Surface Treatment:   | Cadmium Overall                                     |
| Surface Treatment Document And Classification:                 | Qq-p-416 Fed Spec Single Treatment Response Overall |
|  |   |

## **How to Order**

Order this self-locking nutplate from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/MS21061L06K">https://military-fasteners.com/nuts/self\_locking+nutplates/MS21061L06K</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/MS21061L06K">https://military-fasteners.com/nuts/self\_locking+nutplates/MS21061L06K</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/MS21061L06K">https://military-fasteners.com/nuts/self\_locking+nutplates/MS21061L06K</a> and selecting the