



Military-Fasteners.com

P/N MS21061L3

Description

thread: 10-32, self locking, one lug floating, low height, cadmium plated, carbon steel, with dry film lube, plain rivet holes, MS21061 series nut

* Manufacturer certifications are shipped with your order FREE of charge


Order this part online

Additional Information

Alternate Part Numbers

[10AD25A306N13](#)

SKU / Model:	MS21061L3
Minimum Qty (MOQ):	25
NSN:	5310-00-778-9480
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS21061L3 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	1.051 Inches Maximum
Nut Height:	0.250 Inches Maximum
Plate Thickness:	0.032 Inches Maximum
Plate Width:	0.290 Inches Minimum And 0.422 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.339 Inches Minimum And 0.349 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.310 Inches Minimum And 0.314 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.190 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/MS21061L3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.