

Description

Thread Size: 19/64", Nut Height: 21/64", Nut Length: 1-25/64", floating nut, dry film lubricant, fine thread, MS21061 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[RF100A5](#)

SKU / Model:	MS21061L5
Minimum Qty (MOQ):	10
NSN:	5310-00-778-9505
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21061L5 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.130 Inches Minimum And 0.135 Inches Maximum
Nut Style:	Plate
Nut Length:	1.396 Inches Maximum
Nut Height:	0.328 Inches Maximum
Plate Thickness:	0.045 Inches Maximum
Plate Width:	0.412 Inches Minimum And 0.641 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.495 Inches Minimum And 0.505 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.310 Inches Minimum And 0.314 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	24
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.312 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/MS21061L5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.