

P/N MS21062L08

Military-Fasteners.com

Description

thread: 8-32, self-locking nutplate, one lug floating, low height, corrosion resistant steel, with dry film lube, plain rivet holes

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

SKU / Model:	MS21062L08
Minimum Qty (MOQ):	10
NSN:	5310-00-778-9161
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS21062L08 Specifications

Thread Class:36Thread Direction:Right-handLocking Fedure::Prevailing Torque All Metal DesignLubrication:Dry Film LubricantMounting Mole Diameter:0.098 Inches Minimum And 0.103 Inches MaximumNut Style:Onson Inches MaximumNut Length:0.50 Inches MaximumNut Height:0.50 Inches MaximumNut Height:0.032 Inches MaximumPlate Wither0.302 Inches MaximumNut Mounting Provision:Straight HolesNut Mounting Provision:200 Inches Minimum And 0.422 Inches MaximumDistance From Aperture Center To Mounting Hole3.39 Inches Minimum And 0.349 Inches MaximumPlate Wither0.302 Inches Minimum And 0.349 Inches MaximumCenter To Center Distance Between Mounting Hole School Des Fahrenheit Nominal3.30 Inches Minimum And 0.314 Inches MaximumThread Series:0.100 Ers Fahrenheit NominalThread Series:0.100 Ers Fahrenheit NominalMounting Thread Size:0.100 Ers Fahrenheit NominalThread Series:0.100 Ers Fahrenheit NominalMoning Thread Size:0.100 Ers Fahrenheit NominalMarden Series:0.100 Ers Fahrenheit NominalMoning Thread Size:0.100 Ers Fahrenheit Nominal<		
Locking Feature:Prevailing Torque All Metal DesignLubrication:Dry Film LubricantMounting Hole Diameter:0.098 Inches Minimum And 0.103 Inches MaximumNut Style:PlateNut Length:0.501 Inches MaximumNut Height:0.501 Inches MaximumNut Height:0.202 Inches MaximumPlate Michteria0.202 Inches MaximumNut Metight:0.202 Inches MaximumPlate Michteria0.202 Inches MaximumNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2400 Inches Minimum And 0.422 Inches MaximumCenter:0.303 Inches Minimum And 0.314 Inches MaximumStraight Holes3.301 Inches Minimum And 0.314 Inches MaximumCenter Of Center Distance Between Mounting0.310 Inches Minimum And 0.314 Inches MaximumTemp Rating:0.300 Leg Fahrenheit NominalThread Quantity Per Inch:3.200 Leg Fahrenheit NominalThread Straige:No.000 Leg Fahrenheit NominalThread Straige:0.400 Reckwell C MaximumNominal Thread Straige:0.400 Reckwell C MaximumNomina	Thread Class:	3b
Lubrication:Dry Film LubricantMounting Hole Diameter:0.098 Inches Minimum And 0.103 Inches MaximumNut Style:PlateNut Length:0.50 Inches MaximumNut Height:0.250 Inches MaximumNut Height:0.250 Inches MaximumPlate Thickness:0.032 Inches MaximumPlate Thickness:0.032 Inches MaximumNut Mounting Provision:Straight HolesNut Mounting Provision:Straight HolesDistance From Aperture Center To Mounting Hole.339 Inches Minimum And 0.349 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:.310 Inches Minimum And 0.314 Inches MaximumThread Series:UnicUnic450.0 Deg Fahrenheit NominalThread Series:UnicUnic104 InchesThread Series:9.0 Rockwell C MaximumNomial Thread Size:0.164 InchesNonling Thread Size:0.164 InchesMaterial:Incol Alog OverallMaterial Document And Classification:Straight Alterial Response Overall	Thread Direction:	Right-hand
Nounting Hole Diameter:0.098 Inches Minimum And 0.103 Inches MaximumNut Style:PlateNut Length:0.501 Inches MaximumNut Height:0.502 Inches MaximumPlate Thickness:0.321 Inches MaximumPlate Thickness:0.320 Inches Maximum And 0.422 Inches MaximumPlate With:0.320 Inches Maximum And 0.422 Inches MaximumNut Mounting Provision:Sraight HolesNut Mounting Provision:1046Plate Thickness:0.303 Inches Minimum And 0.349 Inches MaximumBostner From Aperture Center Distance Between Mounting3.301 Inches Minimum And 0.314 Inches MaximumCenter To Center Distance Between Mounting0.301 Inches Minimum And 0.314 Inches MaximumThread Series:0.502 Fahrenheit NominalThread Series:0.502 Fahrenheit NominalThread Series:0.502 Fahrenheit NominalNominal Thread Size:0.164 InchesNominal Thread Size:0.164 InchesMaterial:Incollog GoverallMaterial:Incollog Size Size Size Size Size Size Size Size	Locking Feature:	Prevailing Torque All Metal Design
Nut Style:PlateNut Length:1.051 Inches MaximumNut Height:0.250 Inches MaximumPlate Thickness:0.32 Inches MaximumPlate Thickness:0.32 Inches MaximumPlate Width:0.290 Inches Maximum And 0.422 Inches MaximumNut Mounting Provision:Straight HolesNut Mounting Provision:2 HolesDistance From Aperture Center To Mounting Hole339 Inches Minimum And 0.349 Inches MaximumCenter:0.301 Inches Minimum And 0.349 Inches MaximumBesting:0.301 Inches Minimum And 0.314 Inches MaximumTemp Rating:450.0 Deg Fahrenheit NominalThread Series:UnjcFloating Nut160 Indig NutThread Quantity Per Inch:32Andress Rating:0.164 InchesNominal Thread Size:0.164 InchesMaterial Response Overall Or Assis Staf Single Material Response OverallMaterial Document And Classification:S552 Assn Std Single Material Response Overall	Lubrication:	Dry Film Lubricant
Nut Length:1.051 Inches MaximumNut Height:0.250 Inches MaximumPlate Thickness:0.032 Inches MaximumPlate Width:0.290 Inches Minimum And 0.422 Inches MaximumNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting.339 Inches Minimum And 0.349 Inches MaximumCenter:0.310 Inches Minimum And 0.349 Inches MaximumCenter To Center Distance Between Mounting.310 Inches Minimum And 0.314 Inches MaximumThead Series:UnjcThread Series:UnjcFatterse Provided:Ploating NutMonting Thread Stating:40.0 Rockwell C MaximumNominal Thread Size:0.164 InchesMonting Thread Stating:0.164 InchesMaterial:Inchel Stating Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall	Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Height:0.250 Inches MaximumPlate Thickness:0.032 Inches MaximumPlate Width:0.290 Inches Minimu And 0.422 Inches MaximumNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole3.39 Inches Minimum And 0.349 Inches MaximumCenter To Center Distance Between Mounting0.310 Inches Minimum And 0.314 Inches MaximumTherad Series:0.30. Ope Fahrenheit NominalThread Series:UnjcFatures Provided:10.60 Norkull C MaximumThread Quantity Per Inch:3.16 Nonkull C MaximumMonting Thread Size:0.164 InchesMonting Thread Size:0.164 InchesMaterial:Inche Size Sass Std Single Material Response Overall Or Ams S735 Assn Std Single Material Response Overall	Nut Style:	Plate
Plate Thickness:0.032 Inches MaximumPlate Width:0.290 Inches Minimun And 0.422 Inches MaximumNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.339 Inches Minimum And 0.349 Inches MaximumDistance From Aperture Center Distance Between Mounting Holes Along Length:0.310 Inches Minimum And 0.314 Inches MaximumTemp Rating:450.0 Deg Fahrenheit NominalThread Series:UnjcFatures Provided:Floating NutThread Quantity Per Inch:3Age Rating:0.164 InchesNominal Thread Size:0.164 InchesMaterial:In alloy 660 OverallMaterial:Straige Material Response Overall Or Ams 5735 Assn 5td Single Material Response Overall	Nut Length:	1.051 Inches Maximum
Plate Width:0.290 Inches Minimum And 0.422 Inches MaximumNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.339 Inches Minimum And 0.349 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.310 Inches Minimum And 0.314 Inches MaximumTemp Rating:450.0 Deg Fahrenheit NominalThread Series:InjcFeatures Provided:InjcThread Quantity Per Inch:32Ardness Rating:0.164 InchesNominal Thread Size:0.164 InchesMotarial Document And Classification:S552 Assn Std Single Material Response Overall	Nut Height:	0.250 Inches Maximum
Nut Mounting Provision:Straight HolesMounting Hole Arrangement Style:1 HolesDistance From Aperture Center To Mounting Center:.339 Inches Minimum And 0.349 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:.310 Inches Minimum And 0.314 Inches MaximumTemp Rating:450.0 Deg Fahrenheit NominalThread Series:UnjcFatures Provided:Floating NutThread Quantity Per Inch:32Hardness Rating:0.164 InchesNominal Thread Size:0.164 InchesMaterial:Iron Allog 660 OverallMaterial:Mins 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall	Plate Thickness:	0.032 Inches Maximum
Mounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.339 Inches Minimum And 0.349 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.310 Inches Minimum And 0.314 Inches MaximumTemp Rating:0.310 Inches Minimum And 0.314 Inches MaximumTemp Rating:450.0 Deg Fahrenheit NominalThread Series:UnjcFeatures Provided:Floating NutThread Quantity Per Inch:32Hardness Rating:0.164 InchesNominal Thread Size:0.164 InchesMaterial:Iron Alloy 660 OverallMaterial Document And Classification:S525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall	Plate Width:	0.290 Inches Minimum And 0.422 Inches Maximum
Distance From Aperture Center To Mounting Hole Center:0.339 Inches Minimum And 0.349 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.310 Inches Minimum And 0.314 Inches MaximumTemp Rating:450.0 Deg Fahrenheit NominalTemp Rating:450.0 Deg Fahrenheit NominalThread Series:UnjcFeatures Provided:Foating NutThread Quantity Per Inch:32Hardness Rating:0.164 InchesNominal Thread Size:0.164 InchesMaterial:Iron Alloy 660 OverallMaterial Document And Classification:S525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall	Nut Mounting Provision:	Straight Holes
Center:0.339 Inches Minimum And 0.349 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.310 Inches Minimum And 0.314 Inches MaximumTemp Rating:450.0 Deg Fahrenheit NominalThread Series:UnjcFeatures Provided:Floating NutThread Quantity Per Inch:32Hardness Rating:0.164 InchesNominal Thread Size:0.164 InchesMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ars 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall	Mounting Hole Arrangement Style:	2 Holes
Holes Along Length:0.310 Inches Minimum And 0.314 Inches MaximumTemp Rating:450.0 Deg Fahrenheit NominalThread Series:UnjcFeatures Provided:Floating NutThread Quantity Per Inch:32Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.164 InchesMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall	-	0.339 Inches Minimum And 0.349 Inches Maximum
Thread Series:UnjcFeatures Provided:Floating NutThread Quantity Per Inch:32Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.164 InchesMaterial:Iron Alloy 660 OverallMaterial:S525 Assn Std Single Material Response Overall Overall	-	0.310 Inches Minimum And 0.314 Inches Maximum
Features Provided:Floating NutFread Quantity Per Inch:32Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.164 InchesNaterial:Iron Alloy 660 OverallMaterial:Mats 525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall	Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Quantity Per Inch:32Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.164 InchesNaterial:0.164 InchesMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Ov	Thread Series:	Unjc
Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.164 InchesMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall	Features Provided:	Floating Nut
Nominal Thread Size:0.164 InchesMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall	Thread Quantity Per Inch:	32
Material:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response OverallStatematic Statematic	Hardness Rating:	49.0 Rockwell C Maximum
Material Document And Classification:Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall5737 Assn Std Single Material Response Overall	Nominal Thread Size:	0.164 Inches
Material Document And Classification: 5737 Assn Std Single Material Response Overall	Material:	Iron Alloy 660 Overall
Surface Treatment: Passivate Overall	Material Document And Classification:	
	Surface Treatment:	Passivate Overall

How to Order

Order this self-locking nutplate from our inventory online by visiting <u>https://military-fasteners.com/nuts/self_locking+nutplates/MS21062L08</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.