



★ FASTENERS

Military-Fasteners.com

P/N MS21062L4

## Description

Thread: 1/4-28, Thread Size: 1/4", Nut Height: 9/32", Nut Length: 1-19/64",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS21062L4
Minimum Qty (MOQ):	10
NSN:	5310-00-900-3865
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS21062L4 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Lubrication:</b>	Dry Film Lubricant
<b>Mounting Hole Diameter:</b>	0.098 Inches Minimum And 0.103 Inches Maximum
<b>Nut Style:</b>	Plate
<b>Nut Length:</b>	1.306 Inches Maximum
<b>Nut Height:</b>	0.281 Inches Maximum
<b>Plate Thickness:</b>	0.032 Inches Maximum
<b>Plate Width:</b>	0.350 Inches Minimum And 0.531 Inches Maximum
<b>Nut Mounting Provision:</b>	Straight Holes
<b>Mounting Hole Arrangement Style:</b>	2 Holes
<b>Distance From Aperture Center To Mounting Hole Center:</b>	0.495 Inches Minimum And 0.505 Inches Maximum
<b>Center To Center Distance Between Mounting Holes Along Length:</b>	0.310 Inches Minimum And 0.314 Inches Maximum
<b>Temp Rating:</b>	450.0 Deg Fahrenheit Nominal
<b>Thread Series:</b>	Unjf
<b>Features Provided:</b>	Floating Nut
<b>Thread Quantity Per Inch:</b>	28
<b>Nominal Thread Size:</b>	0.250 Inches
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams5525 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall Or Ams5735 Assn Std Single Material Response Overall

## How to Order

Order this self-locking nutplate from our inventory online by visiting <https://military-fasteners.com/nuts/shear+bolts/MS21062L4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.