



Military-Fasteners.com

P/N MS21062L4

## Description

Thread: 1/4-28, Thread Size: 1/4", Nut Height: 9/32", Nut Length: 1-19/64",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS21062L4
Minimum Qty (MOQ):	10
NSN:	5310-00-900-3865
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

# P/N MS21062L4 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	1.306 Inches Maximum
Nut Height:	0.281 Inches Maximum
Plate Thickness:	0.032 Inches Maximum
Plate Width:	0.350 Inches Minimum And 0.531 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.495 Inches Minimum And 0.505 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.310 Inches Minimum And 0.314 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5525 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall Or Ams5735 Assn Std Single Material Response Overall

## How to Order

Order this self-locking nutplate from our inventory online by visiting <https://military-fasteners.com/nuts/shear+bolts/MS21062L4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.