

Description

thread: 10-32, length: 72", spacing 1.50", self-locking, floating, low height, aluminum channel, cadmium plated carbon steel nuts, dry film lube, 48 nuts

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21063L312
Minimum Qty (MOQ):	1
NSN:	5310-00-915-7982
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts

NO IMAGE
AVAILABLE

P/N MS21063L3-12 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.194 Inches Minimum Nut
Lubrication:	Dry Film Lubricant
Overall Length:	72.000 Inches Nominal
Overall Width:	0.416 Inches Maximum
Nut Style:	Gang Channel, Self Locking
Channel Style:	Straight Type
Assembly Overall Height:	0.250 Inches Maximum
Channel Height:	0.250 Inches Maximum
Nut Spacing:	1.490 Inches Minimum And 1.510 Inches Maximum
Nut Counterbore Depth:	0.062 Inches Minimum Nut
Temp Rating:	250.0 Deg Fahrenheit Maximum
Nut Quantity:	48
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.190 Inches
Material:	Aluminum Alloy Channel
Material:	Steel Nut
Surface Treatment:	Cadmium Nut
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Nut

How to Order

Order this self-locking gang channel nut assembly from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+gang+channel+nut+assemblies/MS21063L3-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.