

## P/N MS21063L3-7-2

## **Description**

Thread Size: 1/4",

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS21063L372

Minimum Qty (MOQ):

NSN: 5310-00-915-7965

Schedule B: 7616.10.9090

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







# P/N MS21063L3-7-2 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.194 Inches Minimum Nut
Lubrication:	Dry Film Lubricant
Overall Length:	72.000 Inches Nominal
Overall Width:	0.416 Inches Maximum
Nut Style:	Gang Channel, Self Locking
Channel Style:	Straight Type
Assembly Overall Height:	0.250 Inches Maximum
Channel Height:	0.250 Inches Maximum
Nut Spacing:	0.865 Inches Minimum And 0.885 Inches Maximum
Nut Counterbore Depth:	0.062 Inches Minimum Nut
Temp Rating:	250.0 Deg Fahrenheit Maximum
Nut Quantity:	82
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.190 Inches
Material:	Aluminum Alloy Channel
Material:	Steel Nut
Surface Treatment:	Cadmium Nut
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Nut

## **How to Order**

Order this self-locking gang channel nut assembly from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+gang+channel+nut+assemblies/MS21063L3-7-2">https://military-fasteners.com/nuts/self\_locking+gang+channel+nut+assemblies/MS21063L3-7-2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.