

Description

Thread Size: 1/4", Length: 72",

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS21063L374 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5310-00-915-7965 |
| Schedule B: | 7616.10.9090 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS21063L3-7-4 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Counterbore Diameter: | 0.194 Inches Minimum Nut |
| Lubrication: | Dry Film Lubricant |
| Overall Length: | 72.000 Inches Nominal |
| Overall Width: | 0.416 Inches Maximum |
| Nut Style: | Gang Channel, Self Locking |
| Channel Style: | Straight Type |
| Assembly Overall Height: | 0.250 Inches Maximum |
| Channel Height: | 0.250 Inches Maximum |
| Nut Spacing: | 0.865 Inches Minimum And 0.885 Inches Maximum |
| Nut Counterbore Depth: | 0.062 Inches Minimum Nut |
| Temp Rating: | 250.0 Deg Fahrenheit Maximum |
| Nut Quantity: | 82 |
| Thread Series: | Unjf |
| Features Provided: | Floating Nut |
| Thread Quantity Per Inch: | 32 |
| Hardness Rating: | 49.0 Rockwell C Maximum |
| Nominal Thread Size: | 0.190 Inches |
| Material: | Aluminum Alloy Channel |
| Material: | Steel Nut |
| Surface Treatment: | Cadmium Nut |
| Surface Treatment Document And Classification: | Qq-p-416 Fed Spec Single Treatment Response Nut |

How to Order

Order this self-locking gang channel nut assembly from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+gang+channel+nut+assemblies/MS21063L3-7-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.