



Military-Fasteners.com

P/N MS21063L3-8-4

Description

Thread Size: 1/4", Length: 4", MS21063 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21063L384
Minimum Qty (MOQ):	5
NSN:	5310-00-915-7968
Schedule B:	8803.30.0030
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS21063L3-8-4 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Counterbore Diameter:</b>	0.194 Inches Minimum Nut
<b>Lubrication:</b>	Dry Film Lubricant
<b>Overall Length:</b>	4.000 Inches Nominal
<b>Overall Width:</b>	0.416 Inches Maximum
<b>Nut Style:</b>	Gang Channel, Self Locking
<b>Channel Style:</b>	Straight Type
<b>Assembly Overall Height:</b>	0.250 Inches Maximum
<b>Channel Height:</b>	0.250 Inches Maximum
<b>Nut Spacing:</b>	0.990 Inches Minimum And 1.010 Inches Maximum
<b>Nut Counterbore Depth:</b>	0.062 Inches Minimum Nut
<b>Temp Rating:</b>	250.0 Deg Fahrenheit Nominal
<b>Nut Quantity:</b>	4
<b>Thread Series:</b>	Unjf
<b>Features Provided:</b>	Floating Nut
<b>Thread Quantity Per Inch:</b>	32
<b>Hardness Rating:</b>	49.0 Rockwell C Maximum
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Material:</b>	Aluminum Alloy Channel
<b>Material:</b>	Steel Nut
<b>Surface Treatment:</b>	Cadmium Nut
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Fed Spec Single Treatment Response Nut

## How to Order

Order this self-locking gang channel nut assembly from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+gang+channel+nut+assemblies/MS21063L3-8-4](https://military-fasteners.com/nuts/self_locking+gang+channel+nut+assemblies/MS21063L3-8-4) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.