

Description

Thread Size: 1/4", Length: 7-7/8", MS21063 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21063L388
Minimum Qty (MOQ):	1
NSN:	5310-00-487-4786
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS21063L3-8-8 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.194 Inches Minimum Nut
Lubrication:	Dry Film Lubricant
Overall Length:	7.936 Inches Nominal
Overall Width:	0.416 Inches Maximum
Nut Style:	Gang Channel, Self Locking
Channel Style:	Straight Type
Assembly Overall Height:	0.250 Inches Maximum
Channel Height:	0.250 Inches Maximum
Nut Spacing:	1.000 Inches Nominal
Nut Counterbore Depth:	0.027 Inches Nominal Nut
Temp Rating:	250.0 Deg Fahrenheit Nominal
Nut Quantity:	8
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.190 Inches
Material:	Aluminum Alloy Channel
Material:	Steel Nut
Surface Treatment:	Cadmium Nut
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Nut

How to Order

Order this self-locking gang channel nut assembly from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+gang+channel+nut+assemblies/MS21063L3-8-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.