

**Description**

self-locking, floating, low height, 6 ft long, aluminum channel, cadmium plated carbon steel nuts, dry film lube, 10-32 thread, 1.125" spacing, maximum 64 nuts

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS21063L39
Minimum Qty (MOQ):	1
NSN:	5310-00-915-7962
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS21063L3-9 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Counterbore Diameter:</b>	0.194 Inches Minimum Nut
<b>Lubrication:</b>	Dry Film Lubricant
<b>Overall Length:</b>	72.000 Inches Nominal
<b>Overall Width:</b>	0.416 Inches Maximum
<b>Nut Style:</b>	Gang Channel, Self Locking
<b>Channel Style:</b>	Straight Type
<b>Assembly Overall Height:</b>	0.250 Inches Maximum
<b>Channel Height:</b>	0.250 Inches Maximum
<b>Nut Spacing:</b>	1.115 Inches Minimum And 1.135 Inches Maximum
<b>Nut Counterbore Depth:</b>	0.062 Inches Minimum Nut
<b>Temp Rating:</b>	250.0 Deg Fahrenheit Nominal
<b>Nut Quantity:</b>	64
<b>Thread Series:</b>	Unjf
<b>Features Provided:</b>	Floating Nut
<b>Thread Quantity Per Inch:</b>	32
<b>Hardness Rating:</b>	49.0 Rockwell C Maximum
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Material:</b>	Aluminum Alloy Channel
<b>Material:</b>	Steel Nut
<b>Surface Treatment:</b>	Cadmium Nut
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Fed Spec Single Treatment Response Nut

## How to Order

Order this self-locking gang channel nut assembly from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+gang+channel+nut+assemblies/MS21063L3-9](https://military-fasteners.com/nuts/self_locking+gang+channel+nut+assemblies/MS21063L3-9) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.