



Military-Fasteners.com

P/N MS21069-5

Description

5/16-24 thread - self-locking nutplate - two lug reduced rivet spacing low height - cadmium plated carbon steel - 450°,, without dry film lube - plain rivet holes

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS210695
Minimum Qty (MOQ):	5
NSN:	5310-00-728-7705
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21069-5 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Soluble Lubricant
Mounting Hole Diameter:	0.130 Inches Minimum And 0.135 Inches Maximum
Nut Style:	Plate
Nut Length:	1.006 Inches Maximum
Nut Height:	0.328 Inches Maximum
Plate Thickness:	0.065 Inches Maximum
Plate Width:	0.475 Inches Minimum And 0.505 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.359 Inches Nominal
Center To Center Distance Between Mounting Holes Along Length:	0.716 Inches Minimum And 0.720 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	24
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.312 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

How to Order

Order this self-locking plate nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/MS21069-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.