

## P/N MS21069L3K

## **Description**

10-32 thread - self-locking nutplate - two lug reduced rivet spacing low height - cadmium plated carbon steel - 450°,, without dry film lube, countersunk rivet holes

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: MS21069L3K

Minimum Qty (MOQ): 25

NSN: 5310-00-728-7723

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS21069L3K Specifications

| Thread Class:  | 3b  |
|--|---|
| Thread Direction:  | Right-hand  |
|  |   |
| Locking Feature:   | Prevailing Torque All Metal Design                            |
| Lubrication:   | Dry Film Lubricant  |
| Mounting Hole Diameter:  | 0.098 Inches Minimum And 0.103 Inches Maximum                 |
| Nut Style:   | Plate   |
| Nut Length:  | 0.724 Inches Maximum  |
| Nut Height:  | 0.250 Inches Maximum  |
| Plate Thickness:   | 0.047 Inches Maximum  |
| Plate Width:   | 0.298 Inches Minimum And 0.328 Inches Maximum                 |
| Nut Mounting Provision:  | Countersunk Holes   |
| Mounting Provision Location:                                   | Opposite Nut Projection Side                                  |
| Mounting Hole Arrangement Style:                               | 2 Holes   |
| Distance From Aperture Center To Mounting Hole Center:         | 0.250 Inches Nominal  |
| Center To Center Distance Between Mounting Holes Along Length: | 0.498 Inches Minimum And 0.502 Inches Maximum                 |
| Temp Rating:   | 450.0 Deg Fahrenheit Nominal                                  |
| Thread Series:   | Unjf  |
| Thread Quantity Per Inch:                                      | 32  |
| Hardness Rating:   | 49.0 Rockwell C Maximum                                       |
| Nominal Thread Size:   | 0.190 Inches  |
| Mounting Hole Countersink Angle:                               | 98.0 Degrees Minimum And 102.0 Degrees Maximum                |
| Material:  | Steel Overall   |
| Surface Treatment:   | Cadmium Overall   |
| Surface Treatment Document And Classification:                 | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |

# **How to Order**

Order this self-locking plate nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/MS21069L3K">https://military-fasteners.com/nuts/self\_locking+nutplates/MS21069L3K</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.