

Description

thread: 3/8-24, self locking, two lug, reduced rivet spacing low height, cadmium plated carbon steel, without dry film lube, plain rivet holes, MS21069 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21069L6
Minimum Qty (MOQ):	10
NSN:	5310-00-728-7719
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21069L6 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.130 Inches Minimum And 0.135 Inches Maximum
Nut Style:	Plate
Nut Length:	1.116 Inches Maximum
Nut Height:	0.344 Inches Maximum
Plate Thickness:	0.075 Inches Maximum
Plate Width:	0.580 Inches Minimum And 0.614 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.414 Inches Nominal
Center To Center Distance Between Mounting Holes Along Length:	0.826 Inches Minimum And 0.830 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	24
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.375 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/MS21069L6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.