

## Description

Thread Size: 1/8", Nut Length: 3/8", Nut Height: 1/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS2107002                                 |
| Minimum Qty (MOQ):      | 10 EA                                     |
| NSN:                    | 5310-00-762-6158                          |
| Schedule B:             | 7318.16.0085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

# P/N MS21070-02 Specifications

|  |  |
|--|--|
| Thread Class:  | 3b   |
| Thread Direction:  | Right-hand   |
| Locking Feature:   | Prevailing Torque All Metal Design   |
| Lubrication:   | Soluble Lubricant  |
| Mounting Hole Diameter:  | 0.066 Inches Minimum And 0.071 Inches Maximum  |
| Nut Style:   | Plate  |
| Nut Length:  | 0.410 Inches Maximum   |
| Nut Height:  | 0.110 Inches Maximum   |
| Plate Thickness:   | 0.035 Inches Maximum   |
| Plate Width:   | 0.140 Inches Minimum And 0.162 Inches Maximum  |
| Nut Mounting Provision:  | Straight Holes   |
| Mounting Hole Arrangement Style:                               | 2 Holes  |
| Distance From Aperture Center To Mounting Hole Center:         | 0.120 Inches Minimum And 0.130 Inches Maximum  |
| Center To Center Distance Between Mounting Holes Along Length: | 0.248 Inches Minimum And 0.252 Inches Maximum  |
| Temp Rating:   | 800.0 Deg Fahrenheit Nominal   |
| Thread Series:   | Unjc   |
| Thread Quantity Per Inch:                                      | 56   |
| Hardness Rating:   | 49.0 Rockwell C Maximum  |
| Nominal Thread Size:   | 0.086 Inches   |
| Material:  | Iron Alloy 660 Overall   |
| Material Document And Classification:                          | Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5525 Assn Std Single Material Response Overall |
| Precious Material:   | Silver   |
| Surface Treatment:   | Silver Overall   |
| Surface Treatment Document And Classification:                 | Ams 2410 Assn Std Single Treatment Response Overall  |

## How to Order

Order this plate - two lug locknut from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+nutplates/MS21070-02](https://military-fasteners.com/nuts/self_locking+nutplates/MS21070-02) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.