

P/N MS21070-4

Description

Thread Size: 1/4", Nut Length: 3/4", Nut Height: 1/4

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS210704
Minimum Qty (MOQ):	10
NSN:	5310-00-762-6137
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS21070-4 Specifications

Thread Direction: Right-hand Prevailing Torque All Metal Design Lubrication: Soluble Lubricant Soluble Lubricant Soluble Lubrication: Soluble Lubricant Mounting Hole Diameter: 0.098 Inches Minimum And 0.103 Inches Maximum Nut Style: Plate Nut Length: 0.786 Inches Maximum Nut Height: 0.786 Inches Maximum Plate Thickness: 0.555 Inches Maximum Plate Thickness: 0.555 Inches Maximum Nut Hounting Provision: Straight Holes Minimum And 0.414 Inches Maximum Nut Mounting Provision: Straight Holes Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Arrangement Style: 0.281 Inches Nominal Center Distance Between Mounting Hole Arrangement Style: 0.560 Inches Minimum And 0.564 Inches Maximum Nut Mounting Provision: Straight Holes Nominal Center Distance Retween Mounting Hole Arrangement Style: 0.560 Inches Minimum And 0.564 Inches Maximum Nut Mounting Hole Arrangement Style: 0.560 Inches Minimum And 0.564 Inches Maximum Nut Mounting Hole Arrangement Style: 0.560 Inches Minimum And 0.564 Inches Maximum Nut Mounting Holes Along Length: 0.560 Inches Minimum And 0.564 Inches Maximum Nut Mounting Holes Along Length: 0.560 Inches Minimum And 0.564 Inches Maximum Nut Mounting Holes Along Length: 0.560 Inches Minimum And 0.564 Inches Maximum Nut Mounting Holes Along Length: 0.560 Inches Minimum And 0.564 Inches Maximum Nut Mounting Holes Along Length: 0.560 Inches Minimum And 0.564 Inches Maximum Nut Mounting Holes Along Length: 0.560 Inches Minimum And 0.564 Inches Maximum Nut Mounting Holes Along Length: 0.560 Inches Minimum And 0.564 Inches Maximum Nut Mounting Holes Along Length: 0.560 Inches Minimum And 0.564 Inches Maximum Nut Mounting Holes Along Length: 0.560 Inches Minimum And 0.564 Inches Maximum Nut Mounting Holes Along Length Holes Along Length Holes Maximum Nut Mounting Holes Along Length Holes Maximum Nut Mounting Holes Maximum Nut Mounti		
Locking Feature: Prevailing Torque All Metal Design Lubrication: Soluble Lubricant Mounting Hole Dlameter: 0.098 Inches Minimum And 0.103 Inches Maximum Nut Style: Plate Nut Length: 0.786 Inches Maximum Nut Height: 0.281 Inches Maximum Plate Thickness: 0.55 Inches Maximum Plate Width: 0.380 Inches Minimum And 0.414 Inches Maximum Nut Mounting Provision: 5 Kraight Holes Mut Mounting Provision: 2 Holes Mounting Hole Arrangement Style: 2 Holes Center: 2 Solutions Nominal Center To Center Distance Between Mounting Hole Arrangement Style: 2.821 Inches Nominal Center To Center Distance Between Mounting Holes Along Length: 0.580 Inches Minimum And 0.564 Inches Maximum Holes Along Length: 800.0 Deg Fahrenheit Nominal Thread Series: Unif Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 49.0 Rockwell C Maximum Nominal Thread Size: 49.0 Rockwell C Maximum Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Res	Thread Class:	3b
Lubrication: Soluble Lubricant Mounting Hole Diameter: 0.998 Inches Minimum And 0.103 Inches Maximum Nut Style: Plate Nut Length: 0.786 Inches Maximum Nut Height: 0.281 Inches Maximum Plate Thickness: 0.055 Inches Maximum Plate Width: 0.380 Inches Minimum And 0.414 Inches Maximum Nut Mounting Provision: 1.50 Inches Minimum And 0.414 Inches Maximum Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.281 Inches Nominal Center To Center Distance Between Mounting Holes Along Length: 0.560 Inches Minimum And 0.564 Inches Maximum Bloos Along Length: 800.0 Deg Fahrenheit Nominal Thread Series: Unif Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response	Thread Direction:	Right-hand
Mounting Hole Diameter: 0.098 Inches Minimum And 0.103 Inches Maximum Nut Style: Plate Nut Length: 0.786 Inches Maximum Nut Height: 0.281 Inches Maximum Plate Thickness: 0.055 Inches Maximum Plate Width: 0.380 Inches Minimum And 0.414 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.281 Inches Nominal Center To Center Distance Between Mounting Holes Along Length: 0.560 Inches Minimum And 0.564 Inches Maximum Holes Along Length: 0.560 Inches Minimum And 0.564 Inches Maximum Thread Series: Unjf Thread Quantity Per Inch: 28 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Overall	Locking Feature:	Prevailing Torque All Metal Design
Nut Style: Plate Nut Length: 0.786 Inches Maximum Nut Height: 0.281 Inches Maximum Plate Thickness: 0.055 Inches Maximum Plate Width: 0.380 Inches Minimum And 0.414 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.281 Inches Nominal Center TO Center Distance Between Mounting Holes Along Length: 0.560 Inches Minimum And 0.564 Inches Maximum Tomp Asting: 0.00.0 Deg Fahrenheit Nominal Thread Series: 0.10rf Thread Quantity Per Inch: 28 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: 3557 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response O	Lubrication:	Soluble Lubricant
Nut Length: 0.786 Inches Maximum Nut Height: 0.281 Inches Maximum Plate Thickness: 0.055 Inches Maximum Plate Width: 0.380 Inches Minimum And 0.414 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.281 Inches Nominal Center To Center Distance Between Mounting Holes Along Length: 0.560 Inches Minimum And 0.564 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Thread Quantity Per Inch: 28 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: 5525 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Height: 0.281 Inches Maximum Plate Thickness: 0.055 Inches Maximum Plate Width: 0.380 Inches Minimum And 0.414 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.281 Inches Nominal Center To Center Distance Between Mounting Holes Along Length: 0.560 Inches Minimum And 0.564 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Thread Quantity Per Inch: 28 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Si735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver	Nut Style:	Plate
Plate Thickness: 0.055 Inches Maximum Plate Width: 0.380 Inches Minimum And 0.414 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.281 Inches Nominal Center To Center Distance Between Mounting Holes Along Length: 0.560 Inches Minimum And 0.564 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Thread Quantity Per Inch: 28 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Nut Length:	0.786 Inches Maximum
Plate Width: 0.380 Inches Minimum And 0.414 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.281 Inches Nominal Center To Center Distance Between Mounting Holes Along Length: 0.560 Inches Minimum And 0.564 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Nut Height:	0.281 Inches Maximum
Nut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.281 Inches NominalCenter To Center Distance Between Mounting Holes Along Length:0.560 Inches Minimum And 0.564 Inches MaximumTemp Rating:800.0 Deg Fahrenheit NominalThread Series:UnjfThread Quantity Per Inch:28Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.250 InchesMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall	Plate Thickness:	0.055 Inches Maximum
Mounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.281 Inches NominalCenter To Center Distance Between Mounting Holes Along Length:0.560 Inches Minimum And 0.564 Inches MaximumTemp Rating:800.0 Deg Fahrenheit NominalThread Series:UnjfThread Quantity Per Inch:28Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.250 InchesMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall	Plate Width:	0.380 Inches Minimum And 0.414 Inches Maximum
Distance From Aperture Center To Mounting Hole Center: 0.281 Inches Nominal Center To Center Distance Between Mounting Holes Along Length: 0.560 Inches Minimum And 0.564 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Thread Quantity Per Inch: 28 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Nut Mounting Provision:	Straight Holes
Center:0.281 Inches NominalCenter To Center Distance Between Mounting Holes Along Length:0.560 Inches Minimum And 0.564 Inches MaximumTemp Rating:800.0 Deg Fahrenheit NominalThread Series:UnjfThread Quantity Per Inch:28Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.250 InchesMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall	Mounting Hole Arrangement Style:	2 Holes
Holes Along Length: Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Thread Quantity Per Inch: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall		0.281 Inches Nominal
Thread Series: Unjf Thread Quantity Per Inch: 28 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	_	0.560 Inches Minimum And 0.564 Inches Maximum
Thread Quantity Per Inch: Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Iron Alloy 660 Overall Material: Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Silver Overall	Temp Rating:	800.0 Deg Fahrenheit Nominal
Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Thread Series:	Unjf
Nominal Thread Size: Material: Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5525 Assn Std Single Material Response Overall Precious Material: Silver Silver Overall	Thread Quantity Per Inch:	28
Material:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall	Hardness Rating:	49.0 Rockwell C Maximum
Material Document And Classification:Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5525 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall	Nominal Thread Size:	0.250 Inches
Precious Material: Surface Treatment: 5525 Assn Std Single Material Response Overall Silver Silver Overall	Material:	Iron Alloy 660 Overall
Surface Treatment: Silver Overall	Material Document And Classification:	
	Precious Material:	Silver
Surface Treatment Document And Classification: Ams 2410 Assn Std Single Treatment Response Overall	Surface Treatment:	Silver Overall
	Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall

How to Order

