

Description

Thread Size: 1/4", Nut Length: 1", Nut Height: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS210705
Minimum Qty (MOQ):	5 EA
NSN:	5310-00-762-6136
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



* See page 2 for technical characteristics

P/N MS21070-5 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Soluble Lubricant
Mounting Hole Diameter:	0.130 Inches Minimum And 0.135 Inches Maximum
Nut Style:	Plate
Nut Length:	1.006 Inches Maximum
Nut Height:	0.328 Inches Maximum
Plate Thickness:	0.065 Inches Maximum
Plate Width:	0.475 Inches Minimum And 0.505 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.359 Inches Nominal
Center To Center Distance Between Mounting Holes Along Length:	0.716 Inches Minimum And 0.720 Inches Maximum
Temp Rating:	800.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	24
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.312 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5525 Assn Std Single Material Response Overall
Precious Material:	Silver
Surface Treatment:	Silver Overall
Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall

How to Order

Order this plate - two lug locknut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/MS21070-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.