


Description

Thread Size: 1/4", Nut Length: 51/64", Nut Height: 9/32

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS21070L4
Minimum Qty (MOQ):	10
NSN:	5310-00-728-9459
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21070L4 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.786 Inches Maximum
Nut Height:	0.281 Inches Maximum
Plate Thickness:	0.055 Inches Maximum
Plate Width:	0.380 Inches Minimum And 0.414 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.281 Inches Nominal
Center To Center Distance Between Mounting Holes Along Length:	0.560 Inches Minimum And 0.564 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	28
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.250 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/MS21070L4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.