

P/N MS21071-04

Description

MS21071-04 Self-Locking Nutplate

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS2107104

Minimum Qty (MOQ): 20

NSN: 5310-01-044-0770

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS21071-04 Specifications

| Thread Class: | 3b |
|--|---|
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Lubrication: | Soluble Lubricant |
| Mounting Hole Diameter: | 0.098 Inches Minimum And 0.103 Inches Maximum |
| Nut Style: | Plate |
| Nut Length: | 0.667 Inches Maximum |
| Nut Height: | 0.143 Inches Maximum |
| Plate Thickness: | 0.040 Inches Maximum |
| Plate Width: | 0.140 Inches Minimum And 0.260 Inches Maximum |
| Nut Mounting Provision: | Straight Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.198 Inches Minimum And 0.208 Inches Maximum |
| Center To Center Distance Between Mounting Holes Along Length: | 0.217 Inches Minimum And 0.221 Inches Maximum |
| Temp Rating: | 450.0 Deg Fahrenheit Nominal |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall |

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/MS21071-04 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.