

## P/N MS21071-6

### **Description**

MS21071-6 Self-Locking Nutplate

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS210716

Minimum Qty (MOQ): 25

NSN: 5310-01-124-5791

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS21071-6 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Mounting Hole Diameter:	0.130 Inches Minimum And 0.135 Inches Maximum
Nut Style:	Plate
Nut Length:	1.139 Inches Maximum
Nut Height:	0.344 Inches Maximum
Plate Thickness:	0.075 Inches Maximum
Plate Width:	0.580 Inches Minimum And 0.614 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.409 Inches Minimum And 0.419 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.267 Inches Minimum And 0.271 Inches Maximum
Temp Rating:	450.0 Deg Celsius Nominal
Thread Series:	Unf
Thread Quantity Per Inch:	24
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.375 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Type 2 Class 3 Fed Spec All Treatment Responses Overall

## **How to Order**

Order this self-locking nutplate from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/MS21071-6">https://military-fasteners.com/nuts/self\_locking+nutplates/MS21071-6</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outher to complete your order.