

P/N MS21071L08K

Military-Fasteners.com

Description

8-32 thread - self-locking nutplate - one lug reduced rivet spacing low height - cadmium plated carbon steel - 450°,, without dry film lube, countersunk rivet holes

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

SKU / Model:	MS21071L08K
Minimum Qty (MOQ):	10
NSN:	5310-00-764-1758
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS21071L08K Specifications

Thread Direction:Right-handLocking Feature:Prevailing Torque All Metal DesignCounterbore Diameter:0.168 Inches Minimum NutLubrication:Dry Film LubricantMounting Hole Diameter:0.098 Inches Minimum And 0.103 Inches MaximumNut Style:PlateNut Height:0.205 Inches MaximumNut Height:0.205 Inches MaximumPlate Thickness:0.047 Inches MaximumPlate Width:0.235 Inches MaximumNut Meight:0.029 Inches MaximumNut Muthig Provision:0.062 Inches MaximumNut Muthig Provision:0.062 Inches Maximum NutNut Muthig Provision:0.099 Inches MaximumNut Mounting Provision:0.090 Inches MaximumMounting Provision Location:0.090 Inches MaximumMounting Provision Location:0.022 Inches MaximumCenter Distance Between Mounting Hole Center:0.229 Inches Minimum And 0.239 Inches MaximumCenter Distance Between Mounting Hole Salong Length:0.210 Inches Minimum And 0.231 Inches MaximumThread Quantity Per Inch:32Hardness Rating:0.09 Rockwell C MaximumNominal Thread Size:0.164 InchesMounting Hole Countersink Angle:98.0 Degrees Minimum And 0.20.0 Degrees MaximumMaterial:Steel OverailSurface Treatment And Classification:0.44 Inches	Thread Class:	3b
Locking Feature:Prevailing Torque All Metal DesignCounterbore Diameter:0.168 Inches Minimun NutLubrication:0.79 Film LubricantMounting Hole Diameter:0.998 Inches Minimun And 0.103 Inches MaximumNut Style:PlateNut Length:0.716 Inches MaximumNut Length:0.716 Inches MaximumNut Length:0.725 Inches MaximumPlate Thickness:0.407 Inches MaximumPlate Width:0.235 Inches Minimun Nut 0.297 Inches MaximumNut Counterbore Depth:0.252 Inches Minimun Nut 0.297 Inches MaximumNut Counterbore Depth:0.062 Inches Minimun Nut 0.297 Inches MaximumNut Counterbore Depth:0.062 Inches Minimun Nut 0.297 Inches MaximumMounting Provision Location:Opposite Nut Projection SideMounting Hole Arrangement Style:219 Inches Minimun And 0.297 Inches MaximumDistance From Aperture Center To Mounting Hole Center:0.229 Inches Minimun And 0.291 Inches MaximumThread Series:UniceThread Series:UniceThread Series:UniceNurding Hole Countersink Angle:9.0 Rockwell C MaximumNominal Thread Stize:0.161 InchesMounting Hole Countersink Angle:9.0 Rockwell C MaximumNominal Thread Stize:0.164 InchesMounting Hole Countersink Angle:8.0 Degrees Minimun And 0.20 Degrees MaximumMounting Hole Countersink Angle:8.0 Degrees Minimum And 0.20 Degrees MaximumMounting Hole Countersink Angle:8.0 Degrees Minimum And 0.20 Degrees MaximumMounting Hole Countersink Angle:8.0		
Counterbore Diameter:0.168 Inches Minimum NutLubrication:Dry Film LubricantMounting Hole Diameter:0.098 Inches Minimum And 0.103 Inches MaximumNut Style:PlateNut Length:0.716 Inches MaximumNut Height:0.250 Inches MaximumPlate Thickness:0.047 Inches Maximum And 0.297 Inches MaximumPlate Width:0.253 Inches Minimum And 0.297 Inches MaximumNut Counterbore Depth:0.062 Inches Minimum And 0.297 Inches MaximumNut Mounting Provision:Countersunk HolesMounting Provision Location:Opposite Nut Projection SideMounting Hole Arrangement Style:229 Inches Minimum And 0.291 Inches MaximumCherer To Schner Between Mounting Hole Center:0.291 Inches Minimum And 0.291 Inches MaximumThread Series:0.291 Inches Minimum And 0.291 Inches MaximumThread Series:0.291 Inches Minimum And 0.291 Inches MaximumThread Series:UnjcNominal Thread Size:0.302 Inches Minimum And 0.291 Inches MaximumNominal Thread Size:0.302 Inches Minimum And 0.291 Inches MaximumMounting Hole Countersink Angle:8.0 Degrees Minimum And 0.291 Inches MaximumMounting Hole Countersink Angle:8.0 Degrees Minimum And 0.201 Inches MaximumMounting Hole Center:0.291 Inches MaximumMateriai:8.0 Degrees Minimum And 0.291 Inches MaximumMateriai:8.0 Degrees Minimum And 0.201 Degrees MaximumMateriai:8.0 Degrees Minimum And 0.201 Degrees Maximum	Locking Feature:	-
Mounting Hole Diameter:0.098 Inches Minimum And 0.103 Inches MaximumNut Style:PlateNut Length:0.716 Inches MaximumNut Height:0.750 Inches MaximumPlate Thickness:0.047 Inches MaximumPlate Width:0.235 Inches Minimum And 0.297 Inches MaximumNut Conterbore Depth:0.047 Inches Maximum And 0.297 Inches MaximumNut Conterbore Depth:0.025 Inches Minimum And 0.297 Inches MaximumNut Mounting Provision Location:0.025 Inches Minimum And 0.297 Inches MaximumMounting Hole Arrangement Style:0.000 File Nut Projection SideMounting Hole Arrangement Style:0.229 Inches Minimum And 0.239 Inches MaximumCenter Distance Between Mounting Hole Schlong Length:0.217 Inches Minimum And 0.211 Inches MinimumTemp Rating:0.217 Inches Minimum And 0.221 Inches MaximumTemp Rating:0.217 Inches Minimum And 0.221 Inches MaximumThread Quantity Per Inch:32Nominal Thread Size:0.164 InchesMounting Hole Countersink Angle:94.0 Rockwell C MaximumNominal Thread Size:0.164 InchesMounting Hole Countersink Angle:94.0 Sogeres Minimum And 10.2.0 Degrees MaximumMounting Hole Countersink Angle:94.0 Rockwell C MaximumMaterial:Stel Overall		
Nut Style:PlateNut Length:0.716 Inches MaximumNut Height:0.250 Inches MaximumPlate Thickness:0.47 Inches MaximumPlate Width:0.235 Inches Minimum And 0.297 Inches MaximumNut Counterbore Depth:0.622 Inches Minimum And 0.297 Inches MaximumNut Counterbore Depth:0.622 Inches Minimum And 0.297 Inches MaximumNut Mounting Provision:Countersunk HolesMounting Provision Location:Opposite Nut Projection SideMounting Hole Arrangement Style:210 Plotes Minimum And 0.239 Inches MaximumDistance From Aperture Center To Mounting Hole Center:0.229 Inches Minimum And 0.239 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.217 Inches Minimum And 0.239 Inches MaximumThread Series:UnjcThread Quantity Per Inch:32Marding Hole Countersink Angle:0.40 Rockwell C MaximumMoming Hole Countersink Angle:0.40 Rockwell C MaximumMounting Hole Countersink Angle:8.00 Degrees Minimum And 102.0 Degrees MaximumMaterial:Steel Overall	Lubrication:	Dry Film Lubricant
Nut Length:0.716 Inches MaximumNut Height:0.250 Inches MaximumPlate Thickness:0.047 Inches MaximumPlate Width:0.253 Inches Minimum And 0.297 Inches MaximumNut Counterbore Depth:0.062 Inches Minimum And 0.297 Inches MaximumNut Counterbore Depth:0.062 Inches Minimum NutNut Mounting Provision:Countersunk HolesMounting Provision Location:Opposite Nut Projection SideMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Holes Along Length:0.229 Inches Minimum And 0.239 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.217 Inches Minimum And 0.221 Inches MaximumTheng Rating:0.020 Rackwell C MaximumThread Quantity Per Inch:32Mounting Hole Countersink Angle:0.164 InchesMounting Hole Countersink Angle:0.164 InchesMaterial:Steel Overall	Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Height:0.250 Inches MaximumPlate Thickness:0.047 Inches MaximumPlate Width:0.235 Inches Minimum And 0.297 Inches MaximumNut Counterbore Depth:0.062 Inches Minimum NutNut Mounting Provision:Countersunk HolesMounting Provision Location:Opposite Nut Projection SideMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.229 Inches Minimum And 0.239 Inches MaximumCenter To Center Distance Between Mounting Hole Salong Length:0.217 Inches Minimum And 0.221 Inches MaximumTemp Rating:UnjcThread Series:UnjcMounting Hole Countersink Angle:9.0 Rockwell C MaximumNominal Thread Size:0.164 InchesMounting Hole Countersink Angle:98.0 Degrees Minimum And 102.0 Degrees MaximumMounting Hole Countersink Angle:Scel Overall	Nut Style:	Plate
Plate Thickness:0.047 Inches MaximumPlate Width:0.235 Inches Minimum And 0.297 Inches MaximumNut Counterbore Depth:0.062 Inches Minimum NutNut Mounting Provision:Countersunk HolesMounting Provision Location:Opposite Nut Projection SideMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Along Length:0.229 Inches Minimum And 0.239 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.217 Inches Minimum And 0.221 Inches MaximumTemp Rating:450.0 Deg Fahrenheit NominalThread Series:UnjcThread Stize:0.164 InchesMounting Hole Countersink Angle:98.0 Degrees Minimum And 102.0 Degrees MaximumMaterial:Steel Overall	Nut Length:	0.716 Inches Maximum
Plate Width:0.235 Inches Minimu And 0.297 Inches MaximumNut Counterbore Depth:0.062 Inches Minimu NutNut Mounting Provision:Countersunk HolesMounting Provision Location:Opposite Nut Projection SideMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.229 Inches Minimu And 0.239 Inches MaximumCenter To Center Distance Between Mounting Hole Along Length:0.217 Inches Minimu And 0.231 Inches MaximumTemp Rating:450.0 Deg Fahrenheit NominalThread Series:UnicThread Quantity Per Inch:32Nominal Thread Size:0.164 InchesMounting Hole Countersink Angle:98.0 Degrees Minimu And 102.0 Degrees MaximumMaterial:Steel Overall	Nut Height:	0.250 Inches Maximum
Nut Counterbore Depth:0.062 Inches Minimum NutNut Mounting Provision:0.062 Inches Minimum NutMounting Provision Location:Countersunk HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.229 Inches Minimum And 0.239 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.217 Inches Minimum And 0.221 Inches MaximumTemp Rating:450.0 Deg Fahrenheit NominalThread Series:UnjcThread Quantity Per Inch:32Nominal Thread Size:0.164 InchesMounting Hole Countersink Angle:98.0 Degrees Minimum And 102.0 Degrees MaximumMounting Hole Countersink Angle:Steel Overall	Plate Thickness:	0.047 Inches Maximum
Nut Mounting Provision:Countersunk HolesMounting Provision Location:Opposite Nut Projection SideMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.229 Inches Minimum And 0.239 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.217 Inches Minimum And 0.231 Inches MaximumTemp Rating:0.217 Inches Minimum And 0.221 Inches MaximumThread Series:UnjcThread Quantity Per Inch:32Hardness Rating:0.164 InchesNominal Thread Size:0.164 InchesMounting Hole Countersink Angle:98.0 Degrees Minimum And 102.0 Degrees MaximumMaterial:Steel OverallSurface Treatment:Contersile Angle	Plate Width:	0.235 Inches Minimum And 0.297 Inches Maximum
Mounting Provision Location:Opposite Nut Projection SideMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.229 Inches Minimum And 0.239 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.217 Inches Minimum And 0.221 Inches MaximumTemp Rating:450.0 Deg Fahrenheit NominalThread Series:UnjcThread Quantity Per Inch:32Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.164 InchesMounting Hole Countersink Angle:98.0 Degrees Minimum And 102.0 Degrees MaximumMaterial:Steel Overall	Nut Counterbore Depth:	0.062 Inches Minimum Nut
Mounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.229 Inches Minimum And 0.239 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.217 Inches Minimum And 0.221 Inches MaximumTemp Rating:450.0 Deg Fahrenheit NominalThread Series:UnjcThread Quantity Per Inch:32Hardness Rating:0.164 InchesNominal Thread Size:0.164 InchesMounting Hole Countersink Angle:98.0 Degrees Minimum And 102.0 Degrees MaximumMaterial:Steel Overall	Nut Mounting Provision:	Countersunk Holes
Distance From Aperture Center To Mounting Hole Center:0.229 Inches Minimum And 0.239 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.217 Inches Minimum And 0.221 Inches MaximumTemp Rating:450.0 Deg Fahrenheit NominalThread Series:UnjcThread Quantity Per Inch:32Hardness Rating:0.164 InchesNominal Thread Size:0.164 InchesMounting Hole Countersink Angle:98.0 Degrees Minimum And 102.0 Degrees MaximumMaterial:Steel OverallSurface Treatment:Cadmium Overall	Mounting Provision Location:	Opposite Nut Projection Side
Center Distance Between Mounting Holes Along Length:0.217 Inches Minimum And 0.221 Inches MaximumTemp Rating:450.0 Deg Fahrenheit NominalThread Series:UnjcThread Quantity Per Inch:32Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.164 InchesMounting Hole Countersink Angle:98.0 Degrees Minimum And 102.0 Degrees MaximumMaterial:Steel OverallSurface Treatment:Cadmium Overall	Mounting Hole Arrangement Style:	2 Holes
Temp Rating:450.0 Deg Fahrenheit NominalThread Series:UnjcThread Quantity Per Inch:32Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.164 InchesMounting Hole Countersink Angle:98.0 Degrees Minimum And 102.0 Degrees MaximumMaterial:Steel OverallSurface Treatment:Cadmium Overall	Distance From Aperture Center To Mounting Hole Center:	0.229 Inches Minimum And 0.239 Inches Maximum
Thread Series:UnjcThread Quantity Per Inch:32Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.164 InchesNounting Hole Countersink Angle:98.0 Degrees Minimum And 102.0 Degrees MaximumMaterial:Steel OverallSurface Treatment:Cadmium Overall	Center To Center Distance Between Mounting Holes Along Length:	0.217 Inches Minimum And 0.221 Inches Maximum
Thread Quantity Per Inch:32Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.164 InchesMounting Hole Countersink Angle:98.0 Degrees Minimum And 102.0 Degrees MaximumMaterial:Steel OverallSurface Treatment:Cadmium Overall	Temp Rating:	450.0 Deg Fahrenheit Nominal
Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.164 InchesMounting Hole Countersink Angle:98.0 Degrees Minimum And 102.0 Degrees MaximumMaterial:Steel OverallSurface Treatment:Cadmium Overall	Thread Series:	Unjc
Nominal Thread Size:0.164 InchesMounting Hole Countersink Angle:98.0 Degrees Minimum And 102.0 Degrees MaximumMaterial:Steel OverallSurface Treatment:Cadmium Overall	Thread Quantity Per Inch:	32
Mounting Hole Countersink Angle: 98.0 Degrees Minimum And 102.0 Degrees Maximum Material: Steel Overall Surface Treatment: Cadmium Overall	Hardness Rating:	49.0 Rockwell C Maximum
Material: Steel Overall Surface Treatment: Cadmium Overall	Nominal Thread Size:	0.164 Inches
Surface Treatment: Cadmium Overall	Mounting Hole Countersink Angle:	98.0 Degrees Minimum And 102.0 Degrees Maximum
	Material:	Steel Overall
Surface Treatment Document And Classification: Qq-p-416 Fed Spec Single Treatment Response Overall	Surface Treatment:	Cadmium Overall
	Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Overall

How to Order

Order this self-locking plate nut from our inventory online by visiting <u>https://military-fasteners.com/nuts/self_locking+nutplates/MS21071L08K</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.

Provided by Military-Fasteners.com