

Description

8-32 thread - self-locking nutplate - one lug reduced rivet spacing low height - cadmium plated carbon steel - 450°, without dry film lube, countersunk rivet holes

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21071L08K
Minimum Qty (MOQ):	10
NSN:	5310-00-764-1758
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS21071L08K Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.168 Inches Minimum Nut
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.716 Inches Maximum
Nut Height:	0.250 Inches Maximum
Plate Thickness:	0.047 Inches Maximum
Plate Width:	0.235 Inches Minimum And 0.297 Inches Maximum
Nut Counterbore Depth:	0.062 Inches Minimum Nut
Nut Mounting Provision:	Countersunk Holes
Mounting Provision Location:	Opposite Nut Projection Side
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.229 Inches Minimum And 0.239 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.217 Inches Minimum And 0.221 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjc
Thread Quantity Per Inch:	32
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.164 Inches
Mounting Hole Countersink Angle:	98.0 Degrees Minimum And 102.0 Degrees Maximum
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Overall

How to Order

Order this self-locking plate nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/MS21071L08K and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.