

P/N MS21072-3

Description

MS21072-3 Self-Locking Nutplate

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS210723

Minimum Qty (MOQ): 25

NSN: 5310-00-762-2878

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS21072-3 Specifications

Thread Direction: Locking Feature: Prevailing Torque All Metal Design Mounting Hole Diameter: Nut Style: Plate Nut Length: Nut Height: 0.745 Inches Maximum Nut Height: 0.250 Inches Maximum Nut Height: 0.298 Inches Minimum And 0.328 Inches Maximum Nut Height: Nut Mounting Provision: Nut Mounting Provision: Nut Mounting Provision: Mounting Hole Arrangement Style: Distance From Aperture Center To Mounting Hole Center: Center To Center Distance Between Mounting Holes Along Length: Now Joep Fahrenheit Nominal Thread Series: Unjf Thread Quantity Per Inch: 32 Hardness Rating: Nominal Thread Size: Material: Material Document And Classification: Naterial Response Overall View Coverall View Creatment Scores (Siver Overall View Creatment Scores) View Coverall View Creatment Scores (Siver Overall View Creatment Scores) View Coverall View Creatment Scores (Siver Overall View Creatment Scores) View Coverall View Creatment Scores (Siver Overall View Creatment Scores) View Coverall View Creatment Response Overall View Creatment Response Overall View Coverall View Creatment Response Overall View Creatment Response Overall		
Locking Feature: Prevailing Torque All Metal Design Mounting Hole Diameter: 0.098 Inches Minimum And 0.103 Inches Maximum Nut Style: Plate Nut Length: 0.745 Inches Maximum Nut Height: 0.250 Inches Maximum Plate Width: 0.047 Inches Maximum Plate Width: 0.298 Inches Minimum And 0.328 Inches Maximum Nut Mounting Provision: 5 traight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.245 Inches Minimum And 0.255 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.217 Inches Minimum And 0.221 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unif Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Res	Thread Class:	3b
Mounting Hole Diameter: 0.098 Inches Minimum And 0.103 Inches Maximum Nut Style: Plate Nut Length: 0.745 Inches Maximum Nut Height: 0.250 Inches Maximum Plate Thickness: 0.047 Inches Maximum Plate Wildth: 0.298 Inches Minimum And 0.328 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.245 Inches Minimum And 0.255 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.217 Inches Minimum And 0.221 Inches Maximum Temp Rating: 80.00 Deg Fahrenheit Nominal Thread Quantity Per Inch: 32 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: Iron Alloy 660 Overall Material Document And Classification: 3525 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Overall	Thread Direction:	Right-hand
Nut Style: Plate Nut Length: 0.745 Inches Maximum Nut Height: 0.250 Inches Maximum Plate Thickness: 0.047 Inches Maximum Plate Width: 0.298 Inches Minimum And 0.328 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole 0.245 Inches Minimum And 0.255 Inches Maximum Center To Center Distance Between Mounting 0.217 Inches Minimum And 0.221 Inches Maximum Holes Along Length: 0.217 Inches Minimum And 0.221 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: 100 Inches Material Document And Classification: 5525 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Overall	Locking Feature:	Prevailing Torque All Metal Design
Nut Length: 0.745 Inches Maximum Nut Height: 0.250 Inches Maximum Plate Thickness: 0.047 Inches Maximum Plate Width: 0.298 Inches Minimum And 0.328 Inches Maximum Nut Mounting Provision: 5traight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.245 Inches Minimum And 0.255 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.217 Inches Minimum And 0.221 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Thread Quantity Per Inch: 32 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: Iron Alloy 660 Overall Material Document And Classification: 5525 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Height: 0.250 Inches Maximum Plate Thickness: 0.047 Inches Maximum Plate Width: 0.298 Inches Minimum And 0.328 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.245 Inches Minimum And 0.255 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.217 Inches Minimum And 0.221 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Thread Quantity Per Inch: 32 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver	Nut Style:	Plate
Plate Thickness: 0.047 Inches Maximum Plate Width: 0.298 Inches Minimum And 0.328 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.245 Inches Minimum And 0.255 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.217 Inches Minimum And 0.221 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Thread Quantity Per Inch: 32 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver	Nut Length:	0.745 Inches Maximum
Plate Width: Nut Mounting Provision: Mounting Hole Arrangement Style: Distance From Aperture Center To Mounting Hole Center: Center To Center Distance Between Mounting Holes Along Length: Temp Rating: Number Series: Thread Series: Unjf Thread Quantity Per Inch: Hardness Rating: Nominal Thread Size: Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Nut Height:	0.250 Inches Maximum
Nut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.245 Inches Minimum And 0.255 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.217 Inches Minimum And 0.221 Inches MaximumTemp Rating:800.0 Deg Fahrenheit NominalThread Series:UnjfThread Quantity Per Inch:32Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.190 InchesMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall	Plate Thickness:	0.047 Inches Maximum
Mounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.245 Inches Minimum And 0.255 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.217 Inches Minimum And 0.221 Inches MaximumTemp Rating:800.0 Deg Fahrenheit NominalThread Series:UnjfThread Quantity Per Inch:32Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.190 InchesMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall	Plate Width:	0.298 Inches Minimum And 0.328 Inches Maximum
Distance From Aperture Center To Mounting Hole Center:0.245 Inches Minimum And 0.255 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.217 Inches Minimum And 0.221 Inches MaximumTemp Rating:800.0 Deg Fahrenheit NominalThread Series:UnjfThread Quantity Per Inch:32Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.190 InchesMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall	Nut Mounting Provision:	Straight Holes
Center: Center To Center Distance Between Mounting Holes Along Length: Temp Rating: 10.217 Inches Minimum And 0.221 Inches Maximum 800.0 Deg Fahrenheit Nominal Thread Series: 10.196 Thread Quantity Per Inch: 129 Hardness Rating: 10.190 Inches Inches Maximum 10.211 Inches Maximum 10.212 Inches Maximum 10.213 Inches Maximum 10.213 Inches Maximum 10.214 Inches Maximum 10.215 Inches Maximum 10.216 Inches Maximum 10.216 Inches Maximum 10.216 Inches Maximum 10.217 Inches Maximum 10.217 Inches Minimum And 0.221 Inches Maximum 10.216 Inches Maximum 10.217 Inches Minimum And 0.221 Inches Maximum 10.217 Inches Maximum 10.217 Inches Minimum And 0.221 Inches Maximum 10.217 Inches Maximum 10.217 Inches Minimum And 0.221 Inches Maximum 10.217 I	Mounting Hole Arrangement Style:	2 Holes
Holes Along Length: Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Thread Quantity Per Inch: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	-	0.245 Inches Minimum And 0.255 Inches Maximum
Thread Series: Unjf Thread Quantity Per Inch: 32 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	_	0.217 Inches Minimum And 0.221 Inches Maximum
Thread Quantity Per Inch: Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Temp Rating:	800.0 Deg Fahrenheit Nominal
Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Thread Series:	Unjf
Nominal Thread Size: Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Thread Quantity Per Inch:	32
Material:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall	Hardness Rating:	49.0 Rockwell C Maximum
Material Document And Classification:Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5525 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall	Nominal Thread Size:	0.190 Inches
Material Document And Classification: 5525 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Material:	Iron Alloy 660 Overall
Surface Treatment: Silver Overall	Material Document And Classification:	
	Precious Material:	Silver
Surface Treatment Document And Classification: Ams 2410 Assn Std Single Treatment Response Overall	Surface Treatment:	Silver Overall
	Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/MS21072-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.