

P/N MS21072-4

Description

MS21072-4 Self-Locking Nutplate

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS210724

Minimum Qty (MOQ): 25

NSN: 5310-00-762-2879

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS21072-4 Specifications

| Thread Direction: Locking Feature: Prevailing Torque All Metal Design Mounting Hole Diameter: Nut Style: Plate Nut Length: Nut Height: 0.822 Inches Maximum Nut Height: 0.281 Inches Maximum Nut Height: 0.380 Inches Minimum And 0.141 Inches Maximum Nut Height: Nut Munting Provision: Nut Munting Provision: Mounting Hole Arrangement Style: Distance From Aperture Center To Mounting Hole Center: Center To Center Distance Between Mounting Holes Along Length: Holes Along Length: Thread Series: Unjf Thread Series: Unjf Thread Series: Unjf Thread Quantity Per Inch: 28 Hardness Rating: Nominal Thread Size: Material: Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Preclous Material: Surface Treatment Document And Classification: Ams 2410 Assn Std Single Teatment Response Overall Ams 5735 Assn Std Single Teatment Response Overall Ams 2410 Assn Std Single Teatment Response Overall | | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------|-----------------------------------------------------|
| Locking Feature: Prevailing Torque All Metal Design Mounting Hole Diameter: 0.098 Inches Minimum And 0.103 Inches Maximum Nut Style: Plate Nut Length: 0.822 Inches Maximum Nut Height: 0.822 Inches Maximum Plate Thickness: 0.055 Inches Maximum Plate Width: 0.380 Inches Minimum And 0.414 Inches Maximum Nut Mounting Provision: Stright Holes Mounting Hole Arrangement Style: 2 Holes Obstance From Aperture Center To Mounting Hole Center: 0.276 Inches Minimum And 0.286 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.217 Inches Minimum And 0.221 Inches Maximum Theread Series: 0.01 Fe Thread Quantity Per Inch: 80.0 Deg Fahrenheit Nominal Thread Quantity Per Inch: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 A | Thread Class: | 3b |
| Mounting Hole Diameter: 0.098 Inches Minimum And 0.103 Inches Maximum Nut Style: Plate Nut Length: 0.822 Inches Maximum Nut Height: 0.283 Inches Maximum Plate Thickness: 0.055 Inches Maximum Plate Wildth: 0.380 Inches Minimum And 0.414 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.276 Inches Minimum And 0.286 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.217 Inches Minimum And 0.221 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Quantity Per Inch: 28 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: 3525 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Overall | Thread Direction: | Right-hand |
| Nut Style: Plate Nut Length: 0.822 Inches Maximum Nut Height: 0.281 Inches Maximum Plate Thickness: 0.055 Inches Maximum Plate Width: 0.380 Inches Minimum And 0.414 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole 0.276 Inches Minimum And 0.286 Inches Maximum Center To Center Distance Between Mounting 0.217 Inches Minimum And 0.221 Inches Maximum Genter To Center Distance Between Mounting 0.217 Inches Minimum And 0.221 Inches Maximum Holes Along Length: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Thread Series: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: 100 Alloy 660 Overall Material Document And Classification: 5525 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Overall | Locking Feature: | Prevailing Torque All Metal Design |
| Nut Length: 0.821 Inches Maximum Nut Height: 0.281 Inches Maximum Plate Thickness: 0.055 Inches Maximum Plate Width: 0.380 Inches Minimum And 0.414 Inches Maximum Nut Mounting Provision: 5traight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.276 Inches Minimum And 0.286 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.217 Inches Minimum And 0.221 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Thread Quantity Per Inch: 28 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: 5525 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver | Mounting Hole Diameter: | 0.098 Inches Minimum And 0.103 Inches Maximum |
| Nut Height: 0.281 Inches Maximum Plate Thickness: 0.055 Inches Maximum Plate Width: 0.380 Inches Minimum And 0.414 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.276 Inches Minimum And 0.286 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.217 Inches Minimum And 0.221 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Thread Quantity Per Inch: 28 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver | Nut Style: | Plate |
| Plate Thickness: 0.055 Inches Maximum Plate Width: 0.380 Inches Minimum And 0.414 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.276 Inches Minimum And 0.286 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.217 Inches Minimum And 0.221 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Thread Quantity Per Inch: 28 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver | Nut Length: | 0.822 Inches Maximum |
| Plate Width: Nut Mounting Provision: Mounting Hole Arrangement Style: Distance From Aperture Center To Mounting Hole Center: Center To Center Distance Between Mounting Holes Along Length: Temp Rating: Number Series: Unjf Thread Series: Unjf Hardness Rating: Nominal Thread Size: Material: Iron Alloy 660 Overall Ams 5735 Assn Std Single Material Response Overall Precious Material: Silver Silver Overall | Nut Height: | 0.281 Inches Maximum |
| Nut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.276 Inches Minimum And 0.286 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.217 Inches Minimum And 0.221 Inches MaximumTemp Rating:800.0 Deg Fahrenheit NominalThread Series:UnjfThread Quantity Per Inch:28Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.250 InchesMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall | Plate Thickness: | 0.055 Inches Maximum |
| Mounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.276 Inches Minimum And 0.286 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.217 Inches Minimum And 0.221 Inches MaximumTemp Rating:800.0 Deg Fahrenheit NominalThread Series:UnjfThread Quantity Per Inch:28Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.250 InchesMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall | Plate Width: | 0.380 Inches Minimum And 0.414 Inches Maximum |
| Distance From Aperture Center To Mounting Hole Center:0.276 Inches Minimum And 0.286 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.217 Inches Minimum And 0.221 Inches MaximumTemp Rating:800.0 Deg Fahrenheit NominalThread Series:UnjfThread Quantity Per Inch:28Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.250 InchesMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall | Nut Mounting Provision: | Straight Holes |
| Center: Center To Center Distance Between Mounting Holes Along Length: Temp Rating: 10.217 Inches Minimum And 0.221 Inches Maximum 800.0 Deg Fahrenheit Nominal Thread Series: 10.17 Inches Minimum And 0.221 Inches Maximum Thread Series: 10.17 Inches Minimum And 0.221 Inches Maximum Thread Series: 10.17 Inches Minimum And 0.221 Inches Maximum Thread Series: 10.17 Inches Minimum And 0.221 Inches Maximum Thread Series: 10.17 Inches Minimum And 0.221 Inches Maximum 40.0 Deg Fahrenheit Nominal Thread Series: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches 10.250 Inches Minimum And 0.221 Inches Maximum Nominal Thread Size: 10.250 Inches Minimum And 0.221 Inches Maximum Nominal Thread Size: 10.250 Inches Minimum And 0.221 Inches Maximum Nominal Thread Size: 10.250 Inches Minimum And 0.221 Inches Maximum Nominal Thread Size: 10.250 Inches Minimum And 0.221 Inches Maximum Nominal Thread Size: 10.250 Inches Minimum And 0.221 Inches Maximum Nominal Thread Size: 10.250 Inches Minimum And 0.221 Inches Maximum Nominal Thread Size: 10.250 Inches Minimum And 0.221 Inches Maximum Nominal Thread Size: 10.250 Inches Minimum And 0.221 Inches Maximum Nominal Thread Size: 10.250 Inches Minimum And 0.221 Inches Maximum Nominal Thread Size: 10.250 Inches Minimum And 0.221 Inches Maximum Nominal Thread Size: 10.250 Inches Minimum And 0.221 Inches Maximum Nominal Thread Size: 10.250 Inches Minimum And 0.221 Inches Maximum Nominal Thread Size: 10.250 Inches Minimum And 0.221 Inches Maximum Nominal Thread Size: 10.250 Inches Minimum And 0.221 Inches Maximum Nominal Thread Size: 10.250 Inches Minimum And 0.221 Inches Maximum Nominal Thread Size: 10.250 Inches Minimum And 0.221 Inches Maximum Nominal Thread Size: 10.250 Inches Minimum And 0.221 Inches Maximum Nominal Thread Size: 10.250 Inches Minimum And 0.221 Inches Maximum Nominal Thread Size: 10.250 Inches Minimum And 0.221 In | Mounting Hole Arrangement Style: | 2 Holes |
| Holes Along Length: Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Thread Quantity Per Inch: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall | - | 0.276 Inches Minimum And 0.286 Inches Maximum |
| Thread Series: Unjf Thread Quantity Per Inch: 28 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall | _ | 0.217 Inches Minimum And 0.221 Inches Maximum |
| Thread Quantity Per Inch: Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5525 Assn Std Single Material Response Overall Precious Material: Surface Treatment: Silver Overall | Temp Rating: | 800.0 Deg Fahrenheit Nominal |
| Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.250 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall | Thread Series: | Unjf |
| Nominal Thread Size: Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall | Thread Quantity Per Inch: | 28 |
| Material:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall | Hardness Rating: | 49.0 Rockwell C Maximum |
| Material Document And Classification:Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5525 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall | Nominal Thread Size: | 0.250 Inches |
| Material Document And Classification: 5525 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall | Material: | Iron Alloy 660 Overall |
| Surface Treatment: Silver Overall | Material Document And Classification: | |
| | Precious Material: | Silver |
| Surface Treatment Document And Classification: Ams 2410 Assn Std Single Treatment Response Overall | Surface Treatment: | Silver Overall |
| | Surface Treatment Document And Classification: | Ams 2410 Assn Std Single Treatment Response Overall |

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/MS21072-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.