

P/N MS21072-6

Military-Fasteners.com

#### Description

MS21072-6 Self-Locking Nutplate

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

### Order this part online

#### **Additional Information**

SKU / Model:	MS210726
Minimum Qty (MOQ):	25
NSN:	5310-00-762-2881
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



# P/N MS21072-6 Specifications

Thread Class:36Thread Class:96Thread Direction:97Locking Feature:Prevailing Torque All Metal DesignMounting Hole Diameter:0.130 Inches Minimum And 0.135 Inches MaximumNut Style:914Nut Length:0.130 Inches MaximumNut Height:0.341 Inches MaximumPlate Thickness:0.075 Inches MaximumPlate Witht:0.350 Inches Minimum And 0.614 Inches MaximumNut Munting Provision:0.580 Inches Minimum And 0.614 Inches MaximumNut Mounting Hole Arrangement Style:140esDistance From Aperture Center To Mounting Hole2Plate Thickness:0.409 Inches Minimum And 0.419 Inches MaximumCenter To Center Distance Between Mounting0.267 Inches Minimum And 0.419 Inches MaximumCenter Scherer Distance Between Mounting0.90 Deg Fahrenheit NominalThread Quantity Per Inch:0.90 Deg Fahrenheit NominalThread Series:0.91 Rockwell C MaximumNominal Thread Size:0.375 InchesMartini:0.375 InchesMaterial:0.375 InchesMaterial:0.375 InchesMaterial Document And Classification:Silver Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response OverallSturae Treatment:0.80 VorvallSurface Treatment And Classification:Mis 2410 Assn Std Single Treatment Response Overall		
Locking Feature:Prevailing Torque All Metal DesignMounting Hole Diameter:0.130 Inches Minimum And 0.135 Inches MaximumNut Style:PlaeNut Length:0.139 Inches MaximumNut Height:0.344 Inches MaximumPlate Thickness:0.345 Inches MaximumPlate Width:0.580 Inches Minimum And 0.614 Inches MaximumMounting Provision:Stol Stol Sches MaximumMounting Provision:2 HolesDistance From Aperture Center To Mounting Pro4 HolesCenter:0.627 Inches Minimum And 0.419 Inches MaximumBeta Stol Schese Maximum0.627 Inches MaximumPlate Notoning Provision:0.627 Inches Minimum And 0.419 Inches MaximumBeta To Center Distance Between Mounting Provision:0.627 Inches Minimum And 0.271 Inches MaximumTorpa Rating:0.000 Egrafnenheit NominalThread Quantity Per Inch:9.000 Egrafnenheit NominalMarcial Discussification:0.375 InchesMaterial Thread Stree:0.375 InchesMaterial Procuent And Classification:S753 Sass Std Single Material Response Overall Or Ams ST37 Assn Std Single Material Response OverallPrecious Material:Siver OverallPrecious Material:Siver Overall	Thread Class:	3b
Nounting Hole Diameter:0.130 Inches Minimum And 0.135 Inches MaximumNut Style:PlateNut Length:0.139 Inches MaximumNut Height:0.344 Inches MaximumPlate Thickness:0.075 Inches Maximum And 0.614 Inches MaximumPlate Width:0.580 Inches Minimum And 0.614 Inches MaximumNut Mounting Provision:Straight HolesNut Mounting Provision:1.400Plate Thickness:0.075 Inches Maximum And 0.614 Inches MaximumNut Mounting Provision:Straight HolesNut Mounting Provision:1.400Distance From Aperture Center To Mounting Hole.4000 Inches Minimum And 0.419 Inches MaximumCenter Distance Between Mounting Holes Along Length:.027 Inches Minimum And 0.271 Inches MaximumTemp Rating:0.000 Dig Fahrenheit NominalThread Series:0.300 Dig Fahrenheit NominalThread Series:0.375 InchesMounting Thread State:0.375 InchesMaterial:0.375 InchesMaterial:Inches Goverall Or Aming States	Thread Direction:	Right-hand
Nut Style:PlateNut Length:1.139 Inches MaximumNut Height:0.344 Inches MaximumPlate Hickness:0.375 Inches MaximumPlate Width:0.580 Inches Minimum And 0.614 Inches MaximumNut Mounting Provision:Straight HolesNut Mounting Provision:Straight HolesNut Mounting Provision:2 HolesCenter D0.409 Inches Minimum And 0.419 Inches MaximumCenter To Center Distance Between Mounting0.267 Inches Minimum And 0.271 Inches MaximumCenter D0.409 Inches Minimum And 0.271 Inches MaximumTemp Rating:80.0 Deg Fahrenheit NominalThread Series:UnifUnif4.0Hardness Rating:4.0 Rockwell C MaximumNominal Thread Size:0.375 InchesMonting Hock Rating:0.375 InchesMaterial Document And Classification:Straiged Material Response Overall Or Ams 5737 Assn Std Single Material Response OverallPrecious Material:Silver Overall	Locking Feature:	Prevailing Torque All Metal Design
Nut Length:1.39 Inches MaximumNut Height:0.344 Inches MaximumNut Height:0.344 Inches MaximumPlate Thickness:0.075 Inches MaximumPlate Width:0.580 Inches Minimum And 0.614 Inches MaximumNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting HoleAnol 0.419 Inches MaximumCenter:0.409 Inches Minimum And 0.419 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.267 Inches Minimum And 0.271 Inches MaximumThread Series:UnifThread Series:UnifNuminal Thread Size:0.375 InchesMaterial:0.375 InchesMaterial:Inon Alloy 660 OverallMaterial:Inon Alloy 660 OverallPrecious Material:Silver Overall Or Ants 5737 Assn Std Single Material Response Overall Or Ams 5737 Sasn Std Single Material Response OverallPrecious Material:Silver Overall	Mounting Hole Diameter:	0.130 Inches Minimum And 0.135 Inches Maximum
Nut Height:0.344 Inches MaximumPlate Thickness:0.075 Inches MaximumPlate Width:0.580 Inches Minimum And 0.614 Inches MaximumNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole.409 Inches Minimum And 0.419 Inches MaximumCenter To Center Distance Between Mounting.267 Inches Minimum And 0.271 Inches MaximumGenter To Center Distance Between Mounting.267 Inches Minimum And 0.271 Inches MaximumTemp Rating:800.0 Deg Fahrenheit NominalThread Series:UnjfThread Quantity Per Inch:440.0 Rockwell C MaximumNominal Thread Size:0.375 InchesMaterialFon Alloy 660 OverallMaterialFon Alloy 660 OverallPrecious Material:Silver Overall Response Overall Or Ams 5737 Assn Std Single Material Response OverallSurface Treatment:Silver Overall	Nut Style:	Plate
Plate Trickness:0.075 Inches MaximumPlate Width:0.580 Inches Minimum And 0.614 Inches MaximumNut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting HoleA.049 Inches Minimum And 0.419 Inches MaximumCenter Distance Between Mounting.267 Inches Minimum And 0.271 Inches MaximumGenter To Center Distance Between Mounting.267 Inches Minimum And 0.271 Inches MaximumTemp Rating:80.0 Deg Fahrenheit NominalThread Series:UnjfThread Quantity Per Inch:4440.0 Rockwell C MaximumMaterial:0.375 InchesMaterial:Iron Allog 660 OverallMaterial:Iron Str35 Assn Std Single Material Response Overall Or Ams ST37 Assn Std Single Material Response OverallPrecious Material:Silver OverallSurface Treatment:Silver Overall	Nut Length:	1.139 Inches Maximum
Plate With:0.580 Inches Minimum And 0.614 Inches MaximumNut Mounting Provision:5traight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole center:0.409 Inches Minimum And 0.419 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.267 Inches Minimum And 0.271 Inches MaximumTemp Rating:800.0 Deg Fahrenheit NominalThread Series:Uif Accounting 4.00 Rockwell C MaximumMoninal Thread Size:0.375 InchesMoninal Thread Size:0.375 InchesMaterial:Iron Alloy 660 OverallMaterial:Iron Alloy 660 OverallPrecious Material:Silver OverallPrecious Material:Silver Overall	Nut Height:	0.344 Inches Maximum
Nut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting center:0.409 Inches Minimum And 0.419 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.267 Inches Minimum And 0.271 Inches MaximumTemp Rating:800.0 Deg Fahrenheit NominalThread Series:UnjfThread Quantity Per Inch:240.0 Rockwell C Maximum0.375 InchesMaterial:0.375 InchesMaterial:ron Alloy 660 OverallMaterial:ms 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response OverallPrecious Material:Silver OverallSurface Treatment:Silver Overall	Plate Thickness:	0.075 Inches Maximum
Mounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.409 Inches Minimum And 0.419 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.267 Inches Minimum And 0.271 Inches MaximumTemp Rating:800.0 Deg Fahrenheit NominalThread Series:UnjfThread Quantity Per Inch:4Ardness Rating:0.375 InchesNominal Thread Size:0.375 InchesMaterial:Iron Allog 660 OverallMaterial:Iron Allog 660 OverallMaterial Document And Classification:SilverStyle Say Std Single Material Response Overall Or Ams S737 Assn Std Single Material Response OverallStyle Creatment:Silver Overall	Plate Width:	0.580 Inches Minimum And 0.614 Inches Maximum
Distance From Aperture Center To Mounting Hole Center:0.409 Inches Minimum And 0.419 Inches MaximumDistance Between Mounting Holes Along Length:0.267 Inches Minimum And 0.271 Inches MaximumTemp Rating:0.267 Inches Minimum And 0.271 Inches MaximumTemp Rating:0.00 Deg Fahrenheit NominalThread Series:UnjfThread Quantity Per Inch:24Hardness Rating:0.375 InchesNominal Thread Size:0.375 InchesMaterial:Iron Alloy 660 OverallMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Si735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall	Nut Mounting Provision:	Straight Holes
Center:0.409 inches Minimum And 0.419 inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.267 Inches Minimum And 0.271 Inches MaximumTemp Rating:800.0 Deg Fahrenheit NominalThread Series:UnjfThread Quantity Per Inch:24Hardness Rating:9.0 Rockwell C MaximumNominal Thread Size:0.375 InchesMaterial:Iron Alloy 660 OverallMaterial Document And Classification:S735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall	Mounting Hole Arrangement Style:	2 Holes
Holes Along Length:0.267 Inches Minimum And 0.271 Inches MaximumTemp Rating:800.0 Deg Fahrenheit NominalThread Series:UnjfThread Quantity Per Inch:24Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.375 InchesMaterial:Iron Alloy 660 OverallMaterial:Iron Alloy 660 OverallPrecious Material:SilverSurface Treatment:Silver Overall		0.409 Inches Minimum And 0.419 Inches Maximum
Thread Series:UnjfThread Quantity Per Inch:24Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.375 InchesMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall	-	0.267 Inches Minimum And 0.271 Inches Maximum
Thread Quantity Per Inch:24Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.375 InchesMaterial:0.375 InchesMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall	Temp Rating:	800.0 Deg Fahrenheit Nominal
Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.375 InchesMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall	Thread Series:	Unjf
Nominal Thread Size:0.375 InchesMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall	Thread Quantity Per Inch:	24
Material:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall	Hardness Rating:	49.0 Rockwell C Maximum
Material Document And Classification:Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall	Nominal Thread Size:	0.375 Inches
Material Document And Classification: 5525 Assn Std Single Material Response Overall   Precious Material: Silver   Surface Treatment: Silver Overall	Material:	Iron Alloy 660 Overall
Surface Treatment: Silver Overall	Material Document And Classification:	
	Precious Material:	Silver
Surface Treatment Document And Classification: Ams 2410 Assn Std Single Treatment Response Overall	Surface Treatment:	Silver Overall
	Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall

## How to Order

Order this self-locking nutplate from our inventory online by visiting <u>https://military-fasteners.com/nuts/self\_locking+nutplates/MS21072-6</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.