

Description

thread: 10-32, self-locking, one lug reduced rivet spacing, low height, corrosion resistant steel, without dry film lube, plain rivet holes, MS21072 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21072L3
Minimum Qty (MOQ):	20
NSN:	5310-00-762-2887
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21072L3 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.194 Inches Minimum Nut
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.745 Inches Maximum
Nut Height:	0.250 Inches Maximum
Plate Thickness:	0.047 Inches Maximum
Plate Width:	0.298 Inches Minimum And 0.328 Inches Maximum
Nut Counterbore Depth:	0.062 Inches Minimum Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.245 Inches Minimum And 0.255 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.217 Inches Minimum And 0.221 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5525 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/MS21072L3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.