

# P/N MS21073-6

## **Description**

Thread Size: 3/8", Nut Length: 7/8", Nut Height: 3/8

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

## 10AD25A603M21

SKU / Model: MS210736

Minimum Qty (MOQ): 10

NSN: 5310-00-761-3709

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)













<sup>\*</sup> See page 2 for technical characteristics

# P/N MS21073-6 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.379 Inches Minimum Nut
Lubrication:	Soluble Lubricant
Mounting Hole Diameter:	0.130 Inches Minimum And 0.135 Inches Maximum
Nut Style:	Plate
Nut Length:	0.870 Inches Maximum
Nut Height:	0.344 Inches Maximum
Plate Thickness:	0.075 Inches Maximum
Nut Counterbore Depth:	0.062 Inches Minimum Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.409 Inches Minimum And 0.419 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unf
Thread Quantity Per Inch:	34
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.375 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

## **How to Order**

Order this self-locking nutplate from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self-locking+nutplates/MS21073-6">https://military-fasteners.com/nuts/self-locking+nutplates/MS21073-6</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<a href="https://military-fasteners.com/nuts/self-locking+nutplates/MS21073-6">https://military-fasteners.com/nuts/self-locking+nutplates/MS21073-6</a> and selecting the