

Description

thread: 4-40, self locking corner, reduced rivet spacing low height, cadmium plated carbon steel, with dry film lube, plain rivet holes, MS21073 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------|
| SKU / Model: | MS21073L04 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5310-00-761-6880 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 013540, Alum Nuts |



P/N MS21073L04 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Lubrication: | Dry Film Lubricant |
| Mounting Hole Diameter: | 0.098 Inches Minimum And 0.103 Inches Maximum |
| Nut Style: | Plate |
| Nut Length: | 0.448 Inches Maximum |
| Nut Height: | 0.143 Inches Maximum |
| Plate Thickness: | 0.040 Inches Maximum |
| Nut Mounting Provision: | Straight Holes |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.198 Inches Minimum And 0.208 Inches Maximum |
| Temp Rating: | 450.0 Deg Fahrenheit Nominal |
| Thread Series: | Unjc |
| Thread Quantity Per Inch: | 40 |
| Hardness Rating: | 49.0 Rockwell C Maximum |
| Nominal Thread Size: | 0.112 Inches |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/MS21073L04 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.