

P/N MS21073L3

Description

Thread: 10-32, self locking, corner, reduced rivet spacing, low height, cadmium plated carbon steel, with dry film lube, plain rivet holes, MS21073 series nut

Order this part online

Additional Information

SKU / Model: MS21073L3

Minimum Qty (MOQ): 25

NSN: 5310-00-761-4221

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} Manufacturer certifications are shipped with your order FREE of charge

^{*} See page 2 for technical characteristics

P/N MS21073L3 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.526 Inches Maximum
Nut Height:	0.250 Inches Maximum
Plate Thickness:	0.047 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.245 Inches Minimum And 0.255 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/MS21073L3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outher to complete your order.