

P/N MS21073L3K

Description

10-32 thread, self-locking corner nutplate, reduced rivet spacing low height, cadmium plated carbon steel, with dry film lube, countersunk rivet holes

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS21073L3K

Minimum Qty (MOQ): 25

NSN: 5310-00-763-3948

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)













^{*} See page 2 for technical characteristics

P/N MS21073L3K Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.526 Inches Maximum
Nut Height:	0.250 Inches Maximum
Plate Thickness:	0.047 Inches Maximum
Nut Mounting Provision:	Countersunk Holes
Mounting Provision Location:	Opposite Nut Projection Side
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.245 Inches Minimum And 0.255 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	32
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.190 Inches
Mounting Hole Countersink Angle:	98.0 Degrees Minimum And 102.0 Degrees Maximum
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/MS21073L3K and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/self_locking+nutplates/MS21073L3K and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/self_locking+nutplates/MS21073L3K and selecting the