

Description

thread: 1/4-28, self locking, corner, reduced rivet spacing, low height, cadmium plated carbon steel, with dry film lube, plain rivet holes, MS21073 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21073L4
Minimum Qty (MOQ):	10
NSN:	5310-00-761-6830
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21073L4 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.254 Inches Minimum Nut
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.603 Inches Maximum
Nut Height:	0.281 Inches Maximum
Plate Thickness:	0.055 Inches Maximum
Nut Counterbore Depth:	0.062 Inches Minimum Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.276 Inches Minimum And 0.286 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	28
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.250 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Overall

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/MS21073L4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.