

## P/N MS21075-3N

## **Description**

thread: 10-32, self locking nut, two lug floating, reduced rivet spacing, low height, cadmium plated carbon steel, non dry film lube, without eyelets, MS21075 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

### MS21075-3

SKU / Model: MS210753N

Minimum Qty (MOQ): 25

NSN: 5310-01-285-2784

Schedule B: 7318.16.0030

ECCN: EAR99

National Motor Freight: 093490, Bolt / Nut / Screw / Clips / Fastener / Etc









# P/N MS21075-3N Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.739 Inches Maximum
Nut Height:	0.250 Inches Maximum
Plate Thickness:	0.025 Inches Minimum And 0.090 Inches Maximum
Plate Width:	0.290 Inches Minimum And 0.416 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.250 Inches Minimum And 0.255 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.500 Inches Minimum And 0.502 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.190 Inches
Special Features:	W/o Eyelets
Material:	Steel Comp 1035 Overall Or Steel Comp 1050 Overall Or Steel Comp 4130 Overall Or Steel Comp 1040 Overall Or Steel Comp 1042 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Overall

# **How to Order**

