

Description

2 lug, MS21075 series nut

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS210755N |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5310-01-362-0725 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS21075-5N Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Mounting Hole Diameter: | 0.130 Inches Minimum And 0.135 Inches Maximum |
| Nut Length: | 1.010 Inches Maximum |
| Plate Width: | 0.412 Inches Minimum And 0.581 Inches Maximum |
| Nut Mounting Provision: | Straight Holes |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.177 Inches Minimum And 0.182 Inches Maximum |
| Center To Center Distance Between Mounting Holes Along Length: | 0.354 Inches Minimum And 0.364 Inches Maximum |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 24 |
| Hardness Rating: | 49.0 Rockwell C Maximum |
| Nominal Thread Size: | 0.312 Inches |
| Material: | Steel Comp 1035 Overall Or Steel Comp 1040 Overall Or Steel Comp 1042 Overall Or Steel Comp 1050 Overall Or Steel Comp 4130 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq+416,ty2cl2 Fed Spec Single Treatment Response Overall |

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/MS21075-5N and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.