

## P/N MS21075L08N

### **Description**

Thread: 8-32, two lug, floating, reduced rivet spacing, low height, cadmium plated carbon steel, dry film lube, without eyelets, MS21075 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

MS21075L08 NAS1068RA08 10AD25A087M11

SKU / Model:	MS21075L08N
Minimum Qty (MOQ):	50
NSN:	5310-01-345-1813
Schedule B:	7318.16.0000
ECCN:	EAR99
National Motor Freight:	093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N MS21075L08N Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.707 Inches Maximum
Nut Height:	0.250 Inches Maximum
Plate Thickness:	0.140 Inches Maximum
Plate Width:	0.290 Inches Minimum And 0.367 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.229 Inches Minimum And 0.239 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.463 Inches Minimum And 0.473 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjc
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.164 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

## **How to Order**

Order this self-locking nutplate from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/MS21075L08N">https://military-fasteners.com/nuts/self\_locking+nutplates/MS21075L08N</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.