

Description

Thread: 10-32, self locking, two lug, floating, reduced rivet spacing, low height, cadmium plated carbon steel, dry film lube, without eyelets, black color, MS21075 series nutplate

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS21075L3](#) [MS21075L-3N](#) [1OAD25A307M11](#)

| | |
|-------------------------|---|
| SKU / Model: | MS21075L3N |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5310-01-356-5102 |
| Schedule B: | 7318.16.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS21075L3N Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Pitch Diameters: | +0.1562/+0.1697 Inches |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Lubrication: | Dry Film Lubricant |
| Mounting Hole Diameter: | 0.103 Inches Maximum |
| Nut Style: | Plate |
| Nut Length: | 0.739 Inches Maximum |
| Nut Height: | 0.250 Inches Maximum |
| Plate Thickness: | 0.025 Inches Minimum And 0.090 Inches Maximum |
| Plate Width: | 0.290 Inches Minimum And 0.416 Inches Maximum |
| Nut Mounting Provision: | Straight Holes |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.245 Inches Minimum And 0.255 Inches Maximum |
| Center To Center Distance Between Mounting Holes Along Length: | 0.498 Inches Minimum And 0.502 Inches Maximum |
| Temp Rating: | 450.0 Deg Fahrenheit Maximum |
| Thread Series: | Unjf |
| Features Provided: | Floating Nut |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.190 Inches |
| Material: | Steel Comp 1035 Overall Or Steel Comp 4130 Overall |
| Material Document And Classification: | Ams 5080 Assn Std Single Material Response Overall Or Ams 6350 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/MS21075L3N and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.