

P/N MS21075L4E

Military-Fasteners.com

Description

MS21075 series nut

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | MS21075L4E |
|-------------------------|---|
| Minimum Qty (MOQ): | 10 |
| NSN: | 5310-00-784-8145 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS21075L4E Specifications

| Thread Class: | 3b |
|--|---|
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Lubrication: | Dry Film Lubricant |
| Mounting Hole Diameter: | 0.098 Inches Minimum And 0.103 Inches Maximum |
| Nut Style: | Plate |
| Nut Length: | 0.801 Inches Maximum |
| Nut Height: | 0.281 Inches Maximum |
| Plate Thickness: | 0.140 Inches Maximum |
| Plate Width: | 0.350 Inches Minimum And 0.500 Inches Maximum |
| Nut Mounting Provision: | Straight Holes |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.276 Inches Minimum And 0.286 Inches Maximum |
| Center To Center Distance Between Mounting Holes Along Length: | 0.560 Inches Minimum And 0.564 Inches Maximum |
| Temp Rating: | 450.0 Deg Fahrenheit Nominal |
| Thread Series: | Unjf |
| Features Provided: | Floating Nut |
| Thread Quantity Per Inch: | 28 |
| Hardness Rating: | 49.0 Rockwell C Maximum |
| Nominal Thread Size: | 0.250 Inches |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |

How to Order

Order this self-locking extended washer nut from our inventory online by visiting https://military-

<u>fasteners.com/nuts/self_locking+extended+washer+nuts/MS21075L4E</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.