

P/N MS21075L4N

Description

Thread: 1/4-28, self locking, two lug floating, reduced rivet spacing low height, cadmium plated carbon steel, dry film lube, without eyelets, MS21075 series nut

Order this part online

Additional Information

SKU / Model: MS21075L4N

Minimum Qty (MOQ): 25

NSN: 5310-01-335-4894

Schedule B: 7318.16.0000


ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} Manufacturer certifications are shipped with your order FREE of charge

^{*} See page 2 for technical characteristics

P/N MS21075L4N Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.254 Inches Nominal Nut
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.100 Inches Minimum
Nut Style:	Plate (floating)
Nut Length:	0.801 Inches Maximum
Nut Height:	0.281 Inches Maximum
Plate Thickness:	0.027 Inches Minimum And 0.097 Inches Maximum
Plate Width:	0.350 Inches Minimum And 0.500 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.143 Inches Nominal
Center To Center Distance Between Mounting Holes Along Length:	0.286 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	28
Hardness Rating:	40.0 Rockwell C Maximum
Nominal Thread Size:	0.250 Inches
Material:	Steel Comp 1035 Overall Or Steel Comp 4130 Overall Or Steel Comp 1060 Overall Or Steel Comp 1040 Overall Or Steel Comp 1042 Overall
Material Document And Classification:	Aams5080 Assn Std 1st Material Response Overall Or Aams 6350 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Overall

How to Order

