

Description

MS21076-08E Self-Locking Nutplate

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2107608E
Minimum Qty (MOQ):	10
NSN:	5310-01-411-3444
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21076-08E Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.168 Inches Maximum Nut
Overall Height:	0.250 Inches Maximum
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Height:	0.250 Inches Maximum
Plate Thickness:	0.075 Inches Minimum And 0.140 Inches Maximum
Plate Width:	0.290 Inches Minimum And 0.367 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.229 Inches Minimum And 0.239 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.466 Inches Minimum And 0.470 Inches Maximum
Temp Rating:	800.0 Deg Fahrenheit Nominal
Thread Series:	Unjc
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.164 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 552 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Precious Material:	Silver
Surface Treatment:	Silver Overall
Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/MS21076-08E and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.