

P/N MS21076-3

Description

Self-Locking Nutplate, two holes

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS210763

Minimum Qty (MOQ): 25

NSN: 5310-00-775-2567

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS21076-3 Specifications

Thread Direction: Locking Feature: Mounting Hole Diameter: Nut Style: Nut Length: Nut Height: Nut Height: Nut Height: Nut Height: Nut Mounting Provision: Nut Mounting Provision: Nut Mounting Hole Arrangement Style: Distance From Aperture Center To Mounting Hole Center To Center Distance Between Mounting Holes Along Length: Temp Rating: Center To Center Distance Between Mounting Holes Along Length: Thread Series: Christians: Thread Series: Hardness Rating: Asson Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Nateriac Treatment Document And Classification: Ams 2410 Assn Std Single Treatment Response Overall Contract Treatment Document And Classification: Ams 2410 Assn Std Single Treatment Response Overall Christians: Ams 2410 Assn Std Single Treatment Response Overall Christians: Ams 2410 Assn Std Single Treatment Response Overall Christians: Ams 2410 Assn Std Single Treatment Response Overall Christians: Ams 2410 Assn Std Single Treatment Response Overall Christians: C	-, , ,,	
Locking Feature: Prevailing Torque All Metal Design Mounting Hole Diameter: 0.098 Inches Minimum And 0.103 Inches Maximum Nut Style: Plate Nut Length: 0.739 Inches Maximum Nut Height: 0.250 Inches Maximum Plate Thickness: 0.140 Inches Maximum Plate Width: 0.290 Inches Minimum And 0.416 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Arrangement Style: 2 Holes Center Postance Between Mounting Holes Along Length: 0.498 Inches Minimum And 0.255 Inches Maximum Temp Rating: 80.0 Deg Fahrenheit Nominal Thread Series: Unif Features Provided: 1 Floating Nut Thread Quantity Per Inch: 3 Aud Guantity Per Inch: 49.0 Rockwell C Maximum Nominal Thread Size: 1.091 Inches Material Document And Classification: Ams 5525 Asas Std Single Material Response Overall Or Ams 5737 Asas Std Single Material Response Overall Or Ams 5732 Asas Std Single Material Response Overall Or Ams 5732 Asas Std Single Material Response Overall Or Ams 5732 Asas Std Single Material Response Overall Or Ams 5732 Asas Std Single Material Resp	Thread Class:	3b
Mounting Hole Diameter: 0.098 Inches Minimum And 0.103 Inches Maximum Nut Style: Plate Nut Length: 0.739 Inches Maximum Nut Height: 0.250 Inches Maximum Plate Thickness: 0.140 Inches Maximum Plate Width: 0.290 Inches Minimum And 0.416 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole 2.451 Inches Minimum And 0.255 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.498 Inches Minimum And 0.502 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: 90.0 Deg Fahrenheit Nominal Thread Quantity Per Inch: 2 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material Document And Classification: 3m.5525 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Overall	Thread Direction:	Right-hand
Nut Style: Plate Nut Length: 0.739 Inches Maximum Nut Height: 0.250 Inches Maximum Plate Thickness: 0.140 Inches Maximum Plate Width: 0.290 Inches Minimum And 0.416 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.245 Inches Minimum And 0.255 Inches Maximum Center: 0.498 Inches Minimum And 0.502 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 800.0 Deg Fahrenheit Nominal Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unif Features Provided: floating Nut Thread Quantity Per Inch: 32 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: Iron Alloy 660 Overall Material Document And Classification: 3732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5732	Locking Feature:	Prevailing Torque All Metal Design
Nut Length: 0.739 Inches Maximum Nut Height: 0.250 Inches Maximum Plate Thickness: 0.140 Inches Maximum Plate Width: 0.290 Inches Minimum And 0.416 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole 2.451 Inches Minimum And 0.255 Inches Maximum Center To Center Distance Between Mounting 0.498 Inches Minimum And 0.502 Inches Maximum Holes Along Length: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: 19 Idating Nut Thread Quantity Per Inch: 32 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: Iron Alloy 660 Overall Material Document And Classification: 3732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Overall	Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Height: 0.250 Inches Maximum Plate Thickness: 0.140 Inches Maximum Plate Width: 0.290 Inches Minimum And 0.416 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.245 Inches Minimum And 0.255 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.498 Inches Minimum And 0.502 Inches Maximum Temp Rating: 0.498 Inches Minimum And 0.502 Inches Maximum Temp Rating: 0.498 Inches Minimum And 0.502 Inches Maximum Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 32 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: Iron Alloy 660 Overall Material: Iron Alloy 660 Overall Precious Material: Silver Overall Gesponse Overall Or Ams 5737 Assn Std Single Material Response Overall Surface Treatment: Silver Overall	Nut Style:	Plate
Plate Width: 0.140 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.245 Inches Minimum And 0.255 Inches Maximum Center Distance Between Mounting Holes Along Length: 0.498 Inches Minimum And 0.502 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 32 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: 10.10 Inches Material Document And Classification: 2525 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Nut Length:	0.739 Inches Maximum
Plate Width: 0.290 Inches Minimum And 0.416 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.245 Inches Minimum And 0.255 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.498 Inches Minimum And 0.502 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 32 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver	Nut Height:	0.250 Inches Maximum
Nut Mounting Provision:Straight HolesMounting Hole Arrangement Style:2 HolesDistance From Aperture Center To Mounting Hole Center:0.245 Inches Minimum And 0.255 Inches MaximumCenter To Center Distance Between Mounting Holes Along Length:0.498 Inches Minimum And 0.502 Inches MaximumTemp Rating:800.0 Deg Fahrenheit NominalThread Series:UnjfFeatures Provided:Floating NutThread Quantity Per Inch:32Hardness Rating:49.0 Rockwell C MaximumNominal Thread Size:0.190 InchesMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5525 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall	Plate Thickness:	0.140 Inches Maximum
Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.245 Inches Minimum And 0.255 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.498 Inches Minimum And 0.502 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 32 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Plate Width:	0.290 Inches Minimum And 0.416 Inches Maximum
Distance From Aperture Center To Mounting Hole Center: 0.245 Inches Minimum And 0.255 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.498 Inches Minimum And 0.502 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 32 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Nut Mounting Provision:	Straight Holes
Center To Center Distance Between Mounting Holes Along Length: Temp Rating: Number Provided: Floating Nut Thread Quantity Per Inch: Hardness Rating: Nominal Thread Size: Material: Material Document And Classification: Silver Sulver Overall O.498 Inches Minimum And 0.502 Inches Maximum O.498 Inches Maximum O.498 Inches Minimum And 0.502 Inches Maximum O.498 Inches Maximum O.498 Inches Minimum And 0.502 Inches Maximum O.498 Inches Maximum O.498 Inches Minimum And 0.502 Inches Maximum O.498 Inches Maximum O.498 Inches Minimum And 0.502 Inches Maximum O.498 Inches Minimum And 0.502 Inches Maximum O.498 Inches Maximum O.498 Inches Minimum And 0.502 Inches Maximum O.498 Inches Maximum O.498 Inches Minimum And 0.502 Inches Maximum O.498 Inches Maximum O.498 Inches Maximum O.498 Inches Minimum And 0.502 Inches Maximum O.498 Inches	Mounting Hole Arrangement Style:	2 Holes
Holes Along Length: Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 32 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: Iron Alloy 660 Overall Material Document And Classification: 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	-	0.245 Inches Minimum And 0.255 Inches Maximum
Thread Series: Features Provided: Floating Nut Thread Quantity Per Inch: 32 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	_	0.498 Inches Minimum And 0.502 Inches Maximum
Features Provided: Thread Quantity Per Inch: 32 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Temp Rating:	800.0 Deg Fahrenheit Nominal
Thread Quantity Per Inch: Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Thread Series:	Unjf
Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.190 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Features Provided:	Floating Nut
Nominal Thread Size: Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Precious Material: Silver Silver Overall	Thread Quantity Per Inch:	32
Material:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5525 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response OverallPrecious Material:SilverSurface Treatment:Silver Overall	Hardness Rating:	49.0 Rockwell C Maximum
Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Precious Material: Silver Silver Overall	Nominal Thread Size:	0.190 Inches
Precious Material: Surface Treatment: 5732 Assn Std Single Material Response Overall Silver Silver Overall	Material:	Iron Alloy 660 Overall
Surface Treatment: Silver Overall	Material Document And Classification:	
	Precious Material:	Silver
Surface Treatment Document And Classification: Ams 2410 Assn Std Single Treatment Response Overall	Surface Treatment:	Silver Overall
	Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall

How to Order

