

## P/N MS21076-3N

## **Description**

Thread: 10-32, self locking, two lug floating, reduced rivet spacing, low height, corrosion resistant steel, silver plated, without eyelets, MS21076 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

### 10AX86A307M81

SKU / Model:	MS210763N
Minimum Qty (MOQ):	20
NSN:	5310-00-775-2567
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N MS21076-3N Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.739 Inches Maximum
Nut Height:	0.250 Inches Maximum
Plate Thickness:	0.140 Inches Maximum
Plate Width:	0.290 Inches Minimum And 0.416 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.245 Inches Minimum And 0.255 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.498 Inches Minimum And 0.502 Inches Maximum
Temp Rating:	800.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.190 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall
Precious Material:	Silver
Surface Treatment:	Silver Overall

# **How to Order**

