

P/N MS21076L04

Description

two lug, self locking, floating, without eyelets, MS21076 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS21076L04

Minimum Qty (MOQ): 25

NSN: 5310-00-771-7360

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093490, Bolt / Nut / Screw / Clips / Fastener / Etc







^{*} See page 2 for technical characteristics

P/N MS21076L04 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.651 Inches Maximum
Nut Height:	0.153 Inches Maximum
Plate Thickness:	0.140 Inches Maximum
Plate Width:	0.275 Inches Minimum And 0.315 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.198 Inches Minimum And 0.208 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.404 Inches Minimum And 0.408 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjc
Features Provided:	Floating Nut
Thread Quantity Per Inch:	40
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.112 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5525 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/MS21076L04 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.